


Features

- Low Leakage
- Low Forward Voltage Drop
- High Current Capability
- High Speed Switching
- Plastic Material: UL Flammability Classification Rating 94V-0

Mechanical Data

- Case: DO-41, Molded Plastic
- Terminals: Plated Axial Leads, Solderable per MIL-STD-202, Method 208
- Polarity: Color Band Denotes Cathode
- Mounting Position: Any
- Weight: 0.35 grams (approx.)

DISCONTINUED,
NOT RECOMMENDED
FOR NEW DESIGNS,
USE UF1001 - UF1007



DO-41		
Dim	Min	Max
A	25.4	—
B	4.1	5.2
C	0.71	0.86
D	2.0	2.7
All Dimensions in mm		

Maximum Ratings and Electrical Characteristics

Ratings at 25 C ambient temperature unless otherwise specified.
Single phase, half wave, 60Hz, resistive or inductive load.

Characteristic	Symbol	HER 101	HER 102	HER 103	HER 104	HER 105	HER 106	Units
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	300	400	600	V
Maximum RMS Voltage	V_{RMS}	35	70	140	210	280	420	V
Maximum DC Blocking voltage	V_{DC}	50	100	200	300	400	600	V
Maximum Average Forward Rectified Current 9.5mm Lead Length @ $T_A = 50\text{ C}$	$I_{(AV)}$	1.0						A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	I_{FM}	30						A
Maximum Instantaneous Forward Voltage @ 1.0A DC	V_F	1.1					1.75	V
Maximum DC Reverse Current at Rated DC Blocking Voltage	I_R	5.0						A
Maximum DC Reverse Current at Rated DC Blocking Voltage @ $T_A = 150\text{ C}$	I_R	100						A
Maximum Reverse Recovery Time (Note 1)	t_{rr}	50					100	ns
Typical Junction Capacitance (Note 2)	C_j	20						pF
Operating and Storage Temperature Range	T_j, T_{STG}	-65 to +150						C

- Notes: 1. Reverse Recovery Test Conditions: $I_F = 0.5A$, $I_R = 1.0A$, $I_{rr} = 0.25A$
2. Measured at 1.0MHz and applied reverse voltage of 4.0V.

**DISCONTINUED,
NOT RECOMMENDED
FOR NEW DESIGNS,
USE UF1001 - UF1007**




Fig. 1 Typical Forward Current Derating Curve




Fig. 2 Typical Reverse Characteristics




Fig. 3 Typical Instantaneous Forward Characteristics




Fig. 4 Max Non-Repetitive Peak Fwd Surge Current (A)




Fig. 5 Typical Junction Capacitance

IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.

**DISCONTINUED,
NOT RECOMMENDED
FOR NEW DESIGNS,
USE UF1001 - UF1007**