


COPPER SOLUTIONS

★ NEW! **MINI-COM® TX-6™ T3 Module**

- Exceeds all proposed Category 6* requirements including Powersum ACR, ELFEXT and Return Loss
- Delivers headroom over all proposed Category 6 channel requirements
- Features a revolutionary new termination method which speeds installation and reduces conductor untwists to less than 1/2" to provide superior performance
- Can be clearly identified with labels found on page E11-E12
- Can be clearly identified with icons found on page B14
- Black module base designates Category 6 performance with GIGA-TX™ Technology
- Terminates 4-pair 24 and 22 AWG 100 ohm solid unshielded twisted pair cable
- No punchdown tool required, optional termination tool insures conductors are fully terminated




Part Number	Description	No. of Module Spaces	Color‡	Std. Pkg. Qty.	Std. Ctn. Qty.
CJ688T3IW	8 position, 8 wire universal module. Termination cap is color coded for T568A and T568B wiring schemes.	1	Off White	1	50

‡Other colors available. See color chart below.
Also works with modular patch panels found on pages C8-C10.
See page A10 for termination tool.

★ NEW! **MINI-COM TX-6 T3 Shielded Module**

- Terminates 4-pair 24 and 22 AWG 100 ohm solid shielded twisted pair cable



Part Number	Description	No. of Module Spaces	Std. Pkg. Qty.	Std. Ctn. Qty.
CJS688T3	8 position, 8 wire shielded module with one piece shield. Termination cap is color coded for T568A and T568B wiring schemes.	1	1	50

See page A11 for grounding kit.

‡Standard color:		For other colors, substitute IW with:					
IW		EI	WH	IG	BL	OR	
Off White		Elec. Ivory	White	Int. Gray	Black	Orange	
Color shown is approximate.		RD	BU	GR	YL	VL	
		Red	Blue	Green	Yellow	Violet	
		Colors shown are approximate.					

*Proposed Category 6 Industry Specifications