



# LOW PROFILE STRIPS SLW, CES SERIES

Mates with:  
TLW, TSW, MTLW,  
MTSW, EW, ZW

## SPECIFICATIONS

For complete specifications see [www.samtec.com?SLW](http://www.samtec.com?SLW)

**Insulator Material:** Black G.F. Polyester  
**Contact Material:** Phosphor Bronze  
**Plating:** Au or Sn over 50µ" (1,27µm) Ni  
**Current Rating:** 3A  
**Operating Temp Range:** -55°C to +125°C with Gold -55°C to +105°C with Tin  
**Contact Resistance:** 10 mΩ max  
**Insertion Depth:** (2,16mm) .085" to (2,92mm) .115"  
**Insertion Force:** (Single contact only) (3,34N) 12oz avg (0,64mm) .025" SQ pin  
**Withdrawal Force:** (Single contact only) (1,67N) 6 oz avg (0,64mm) .025" SQ pin  
**RoHS Compliant:** Yes  
**Lead-Free Solderable:** Wave only



<b>SLW</b>	<b>1</b>	<b>NO. PINS PER ROW</b>	<b>01</b>	<b>PLATING OPTION</b>	<b>ROW OPTION</b>
<b>01 thru 50</b>				<b>-S</b> = 30µ" (0,76µm) Gold Contact, Matte Tin tail	<b>-S</b> = Single Row
				<b>-G</b> = 20µ" (0,51µm) Gold contact, Gold flash on balance	<b>-D</b> = Double Row
				<b>-T</b> = Matte Tin	

**Note:** Some lengths, styles and options are non-standard, non-returnable.

Mates with:  
TLW, TSW, MTLW,  
MTSW, EW, ZW, DW

## SPECIFICATIONS

For complete specifications see [www.samtec.com?CES](http://www.samtec.com?CES)

**Insulator Material:** Black G.F. Polyester  
**Contact Material:** Phosphor Bronze  
**Plating:** Au or Sn over 50µ" (1,27µm) Ni  
**Current Rating:** 1A  
**Operating Temp Range:** -55°C to +125°C with Gold -55°C to +105°C with Tin  
**Contact Resistance:** 10 mΩ max  
**Insertion Depth:** (2,62mm) .103" to (4,06mm) .160"  
**Insertion Force:** (Single contact only) (2,22N) 8 oz avg (0,64mm) .025" SQ pin  
**Withdrawal Force:** (Single contact only) (1,11N) 4 oz avg (0,64mm) .025" SQ pin  
**RoHS Compliant:** Yes  
**Lead-Free Solderable:** Wave only



<b>CES</b>	<b>1</b>	<b>NO. PINS PER ROW</b>	<b>LEAD STYLE</b>	<b>PLATING OPTION</b>	<b>ROW OPTION</b>	<b>RA OPTION</b>
<b>01 thru 50</b>			<b>-01</b> = (3,05) .120 "A" Dim.	<b>-S</b> = 30µ" (0,76µm) Gold contact, Matte Tin tail	<b>-S</b> = Single Row	<b>-RA</b> = Right Angle version
			<b>-02</b> = (5,46) .215 "A" Dim.	<b>-G</b> = 30µ" (0,76µm) Gold contact, Gold flash on balance	<b>-D</b> = Double Row	Style -02 only Single Row only
				<b>-T</b> = Matte Tin		

**Note:** Some lengths, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)

**SAMTEC USA** • Tel: 1-800-SAMTEC-9 or 812-944-6733 • Fax: 812-948-5047  
**SAMTEC GERMANY** • Tel: +49 (0) 89 / 89460-0 • Fax: +49 (0) 89 / 89460-299  
**SAMTEC JAPAN** • Tel: 045-475-1385 • Fax: 045-475-1340  
**SAMTEC HONG KONG** • Tel: 852-26904858 • Fax: 852-26904842  
**SAMTEC SILICON VALLEY** • Tel: 408-395-5900 • Fax: 408-395-1520  
**SAMTEC FRANCE** • Tel: 01 60 95 06 60 • Fax: 01 60 95 06 61  
**SAMTEC CHINA** • Tel: 86-21-61103766 • Fax: 86-21-53854047  
**SAMTEC SOUTH AFRICA** • Tel: 27 11 4528112 • Fax: 27 86 6714432  
**SAMTEC UK** • Tel: 01236 739292 • Fax: 01236 727113  
**SAMTEC ITALY** • Tel: 39 039 6890337 • Fax: 39 039 6890315  
**SAMTEC INDIA** • Tel: +91-80-3272 1612 • Fax: +91-80-4152 8187  
**SAMTEC TAIWAN** • Tel: 886 02 2698-3367 • Fax: 886 02 8698-2159  
**SAMTEC ANZ** • Tel: 613 9512 7747 • Fax: 613 9512 7745