

Electrical Characteristics (At Ta=25°C, Unless Otherwise Specified)

Type No.	I_R max (μA)	at V_R (V)	P_D (W)	P_{IV} min (V)	V_F max (V)	@ I_F (mA)	I_O (mA)	I_{FM} (mA)
CT21	1	15	0.5	20	1	50	100	400
CT22	1	40	0.5	50	1	50	100	400
CT23	1	90	0.5	100	1	50	100	400
CT24	1	130	0.5	150	1	50	100	400
CT26	1	15	0.5	20	1	100	200	450
CT27	1	40	0.5	50	1	100	200	450
CT28	1	90	0.5	100	1	100	200	450
CT29	1	130	0.5	150	1	100	200	450
CT31	0.1	15	0.5	20	1	50	100	400
CT32	0.1	40	0.5	50	1	50	100	400
CT33	0.1	90	0.5	100	1	50	100	400
CT34	0.1	130	0.5	150	1	50	100	400
CT36	0.1	15	0.5	20	1	100	200	450
CT37	0.1	40	0.5	50	1	100	200	450
CT38	0.1	90	0.5	100	1	100	200	450
CT39	0.1	130	0.5	150	1	100	200	450
CT161	0.25	25	0.5	30	1	15	60	180
CT162	0.25	60	0.5	70	1	5	50	150
CT163	0.25	125	0.5	150	1	1	30	125
CT164	0.25	175	0.5	200	1	3	40	100
CT182	0.25	30	0.5	40	1.1	100	100	400
CT183	0.25	60	0.5	80	1.1	100	100	400
CT184	0.25	125	0.5	150	1.1	100	100	400
CT185	0.25	175	0.5	200	1.1	100	100	400
CT186	0.25	225	0.5	250	1.1	100	100	400
CT187	0.25	300	0.5	325	1.1	100		400
CT256	0.025	25	0.5	30	1	40	90	400
CT257	0.025	60	0.5	70	1	20	75	225
CT258	0.025	125	0.5	150	1	7	55	175



Electrical Characteristics (At Ta=25°C, Unless Otherwise Specified)

Type No.	I_R max (μA)	at V_R (V)	P_D (W)	P_{IV} min (V)	V_F max (V)	@ I_F (mA)	I_O (mA)	I_{FM} (mA)
CT259	0.025	175	0.5	200	1	3	40	125
CT282	0.025	36	0.5	40	1	100	200	650
CT283	0.025	70	0.5	80	1	100	200	650
CT284	0.025	130	0.5	150	1	100	200	650
CT285	0.025	180	0.5	200	1	100	200	650
CT286	0.025	225	0.5	250	1	100	200	650
CT287	0.025	300	0.5	325	1	100	200	650