

ULTRA FAST RECTIFIERS

REVERSE VOLTAGE - **50 to 400** Volts
FORWARD CURRENT - **3.0** Amperes


FEATURES

- Low cost
- Diffused junction
- Ultra fast switching for high efficiency
- Low reverse leakage current
- Low forward voltage drop
- High current capability
- The plastic material carries UL recognition 94V-0

MECHANICAL DATA

- Case : JEDEC DO-201AD molded plastic
- Polarity : Color band denotes cathode
- Weight : 0.04 ounces, 1.1 grams
- Mounting position : Any

DO-201AD



DO-201AD		
Dim.	Min.	Max.
A	25.4	-
B	7.30	9.50
C	1.20	1.30
D	4.80	5.30
All Dimensions in millimeter		

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%

CHARACTERISTICS	SYMBOL	UF3001	UF3002	UF3003	UF3004	UNIT
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	200	400	V
Maximum RMS Voltage	V _{RMS}	35	70	140	280	V
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	V
Maximum Average Forward Rectified Current @T _A =55°C	I _(AV)	3.0				A
Peak Forward Surge Current 8.3ms single half sine-wave super imposed on rated load (JEDEC Method)	I _{FSM}	150				A
Maximum forward Voltage at 3.0A DC	V _F	1.0		1.3		V
Maximum DC Reverse Current at Rated DC Blocking Voltage @T _J =25°C @T _J =100°C	I _R	5 100				uA
Maximum Reverse Recovery Time (Note 1)	T _{RR}	50				ns
Typical Junction Capacitance (Note 2)	C _J	75				pF
Typical Thermal Resistance (Note 3)	R _{θJA}	20				°C/W
Operating Temperature Range	T _J	-55 to +125				°C
Storage Temperature Range	T _{STG}	-55 to +150				°C

NOTES : 1.Measured with I_F=0.5A,I_R=1A,I_{RR}=0.25A.
2.Measured at 1.0MHz and applied reverse voltage of 4.0V DC.
3.Thermal Resistance Junction to Ambient.

