

3.3Vdc HCMOS/TTL SMD CRYSTAL CLOCK OSCILLATOR



ASV1

7.0 x 5.0 x 1.6mm



RoHS
Compliant

ASV1 SERIES

FEATURES:

- Leadless Chip Carrier (LCC)
- HCMOS/TTL Compatible, 3.3Vdc, 2.5Vdc, & 1.8Vdc options
- Reflow capable, Seam Sealed Package

APPLICATIONS:

- Clock signaling for μ Processors, PC Motherboards and Graphic Cards
- High output drive capability (up to 50pf)

STANDARD SPECIFICATIONS:

PARAMETERS	
ABRACON P/N	ASV1 Series
Frequency Range	0.500 MHz to 200.000 MHz
Operating Temperature	-10° C to + 70° C (see options)
Storage Temperature	- 55° C to + 125° C
Overall Frequency Stability	\pm 100 ppm max. (see options)
Supply Voltage (Vdd)	3.3 Vdc \pm 10% (see options)
Input Current	See Table 1
Symmetry	40/60 % max.@ 1/2Vdd (see options)
Rise time / Fall time (Tr/Tf)	See Table 1
Output Load	15pF (10TTL); 50pF max.
Output Voltage	VOH = 0.9 * Vdd min.; VOL = 0.4 Vdc max.
Start-up Time	10ms max.
Tristate Function	"1" (VIH \geq 0.7 Vdc) or open: Oscillation "0" (VIL < 0.3 Vdc) : Hi Z
Disable Current (with Power Down)	10 μ A max.
Disable Current (without Power Down)	200 μ A (Option A)
Enable Time (with Power Down)	400ms max.
Enable Time (without Power Down)	100ns (Option A)
Disable Time (with Power Down)	100ns
Disable Time (without Power Down)	100ns (Option A)
Aging at 25°C/ (first year)	\pm 5 ppm max.
Period Jitter one sigma	1 to 5ps typ. (frequency dependent)


Table 1

Frequency	I _{dd} (max)	Tr/Tf (max)
0.5 ~ 30.0MHz	15mA	10ns
30.01 ~ 70.0MHz	35mA	7ns
70.01~125.0MHz	45mA	7ns
125.01 ~ 165MHz	65mA	5ns

Please contact Abracon for higher frequencies

OPTIONS & PART IDENTIFICATION:

(Left blank if standard)



ABRACON IS
ISO9001:2008
CERTIFIED



Visit www.abracon.com for Terms & Conditions of Sale **Revised: 10.18.10**
30332 Esperanza, Rancho Santa Margarita, California 92688
tel 949-546-8000 | fax 949-546-8001 | www.abracon.com

3.3Vdc HCMOS/TTL SMD CRYSTAL CLOCK OSCILLATOR



ASV1


7.0 x 5.0 x 1.6mm

ASV1 SERIES




RoHS
Compliant


OUTLINE DRAWING:



TAPE & REEL: T = Tape and reel 1,000pcs/reel



REFLOW PROFILE:



ATTENTION: Abracon Corporation's products are COTS - Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

ABRACON IS
ISO9001:2008
CERTIFIED



Visit www.abracon.com for Terms & Conditions of Sale **Revised: 10.18.10**
30332 Esperanza, Rancho Santa Margarita, California 92688
tel 949-546-8000 | fax 949-546-8001 | www.abracon.com