



100044 SERIES

Ordering Information & Typical Technical Characteristics (Ta = 25°C) * Duty Cycle <= 1/10, Pulse Width <= 10msec

PART NUMBER	COLOUR	TYP. FWD VOLTAGE Vf@lopr	MAX FWD VOLTAGE Vf@lopr	FORWARD CURRENT lopr	MAX REV CURRENT lr(Vr=5V)	TYPICAL LUMINOUS INTENSITY Iv@lopr	TYPICAL CHROMATICITY COORDINATES @lopr	VIEWING ANGLE 2ø1⁄2			
OPTICAL/ELECTRICAL CHARACTERISTICS (Ta = 25°C)											
100044	Blue	3.6	4.0	20	50	2300	0.13 / 0.075	15			
UNITS	Water Clear	v	v	mA	uA	mcd	х/у	deg			

UNITS	Water Clear	mA	mA	Vdc	mW	nm	°C	°C			
100044	Blue	30	100	5	120	470	-30 to +85	-40 to +100			
ABSOLUTE MAXIMUM RATINGS (Ta = 25°C)											
PART NUMBER	COLOUR	FORWARD CURRENT lopr max	PEAK FWD CURRENT Ifp *	REVERSE VOLTAGE Vr max	POWER DISSIPATION P dmax	DOM WAVELENGTH Typ. λd	OPERATING TEMP Topr	STORAGE TEMP Tstg			

PRECAUTIONS FOR HANDLING ELECTROSTATIC SENSITIVE LEDs Static Electricity and Surge

Static electricity and surge will damage the LED and a high standard of care must be taken during handling. It is recommended that a wristband, conductive mat or anti-electrostatic glove is used when handling the LEDs. All devices, equipment (e.g. soldering iron points) and machinery must be properly grounded.

SAFETY PRECAUTIONS FOR HANDLING HIGH BRIGHTNESS LEDs

The light output of the Products may cause injuries to human eyes in circumstances where they are viewed directly with unshielded eyes for more than a few seconds.

Please refer to European Standard BSEN 100015-1 1992 for further information.

© MARL OPTOSOURCE 2006 : DS 100044 Issue 1

Telephone +44 (0)1229 582430 • Fax: +44 (0)1229 580012 • email: sales@optosource.com • website: www.optosource.com

The information contained in this datasheet does not constitute part of any order or contract and should not be regarded as a representation relating to either products or service. Marl International reserve the right to alter without notice the specification or any conditions of supply for products or service.