BGA Heat Sink (High Aspect Ratio Ext.) **Straight Fin**





ATS Part#:

Description:

ATS042042011-SF-14J

42.00 x 42.00 x 11.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Straight Fin

Heat Sink Type: Straight Fin Heat Sink Attachment: Equivalent Part Number: N/A

superGRIP

*Image above is for illustration purpose only.

Features & Benefits

- · High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- Features a low profile, slant fin array that offers many of the performance benefits of maxiFLOW™ at a great value .
- . Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks
- Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option ٠

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	6.95 °C/W	4 °C/W	2.9 °C/W	2.3 °C/W	2 °C/W	1.8 °C/W	1.7 °C/W
	Ducted Flow	2.1	1.7	1.5	1.3	1.2	1.2	1.1

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	тім	Finish
	42.00 mm	42.00 mm	11.00 mm	42 mm	N/A	BLACK-ANODIZED
Image above is for illustration purpose only.	 Dimension Dimension Thermal papplication ATS resenses performar ATS certifier 	n D is fin tip to fin tip performance data are n. rves the right to upda nce.	e provided for refere ate or change its pro k assembly is RoHS	m of the base to the nce only. Actual perf ducts without notice 6-6 and REACH com ble.	formanc to impr	e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA