Link Com LinkCom Manufacturing Co., Ltd

| Model NO. | LSP400224001 | Model Name | LED Power Supply |
|-----------|---------------|------------|--|
| Part NO. | PLSP400224001 | SIZE | 132.5 * 58 * 37 mm 【5.22 * 2.28 * 1.46 inch】 |



FEATURES

♦ AC Input 90~264Vac

◆ Protection: SCP / OVP / OCP

♦ High Operating ambient Temp: -20°C ~ +60°C

◆ Safety: UL / PSE

◆ EMC: CE

◆ Comply with Indoor/Outdoor Waterproof (IP 67)

◆ Dimension (L*W*H): 132.5 * 58 * 37 mm◆ Dimension (L*W*H): 5.22 * 2.28 * 1.46 inch

◆ ROHS Compliant

Module : LSP400224001

*,# =SEE NOTES BELOW

| Wodule . L3F400224001 | ,# =SEE NOTES BELOW | | | |
|----------------------------|--|-------|------|--|
| *(O) MODEL | LSP400224001 | | | |
| *(9) SPECIFICATION | min. | norm. | max. | |
| DC OUTPUT VOLTAGE (V) | 18 | | 24 | |
| * PRESET ACCURACY (%) *(8) | | 3 | | |
| * OUTPUT CURRENT(A) *(5) | | | 1.7 | |
| * O/P NOISE (P-P, mV) *(3) | | | 240 | |
| * LINE REGULATION (%) *(7) | | 1 | | |
| * LOAD REGULATION (%) *(6) | | 1 | | |
| DC OUTPUT POWER | 40.8 W | | | |
| EFFICIENCY(typ @Full Load) | 80% at 100Vac/50Hz | | | |
| INPUT VOLTAGE RANGE | 90-264VAC, 127-373VDC, Normal: 100-240VAC | | | |
| INPUT FREQUENCY | Range:47-63Hz, Normal: 50-60Hz | | | |
| INRUSH CURRENT (typ) | COLD START 50A @ 230VAC | | | |
| AC CURRENT | 1A/100VAC | | | |
| LEAKAGE CURRENT | <0.7mA/240VAC | | | |
| SHORT CIRCUIT PROTECTION | short circuit protection will restart automatically after the fault condition is removed | | | |
| OVER CURRENT PROTECTION | Constant Current | | | |
| OVER V, PROTECTION | Shut down and latch off o/p voltage , re-power on to recover | | | |
| * OPERATING TEMP.*(4) | -20 to +60°C @full load | | | |
| STORAGE TEMPERATURE | -40 to +80°C | | | |
| RELATIVE HUMIDITY | 10 to +90%, non-cond. | | | |
| TEMP. COEFFICIENT | 0.03% / °ℂ (0-50°ℂ, typ) | | | |
| SAFETY | UL 1310 / PSE | | | |
| EMI | CE EN55022 | | | |
| DIMENSIONS(L*W*H) | 132.5 * 58 * 37 mm 【5.22 * 2.28 * 1.46 inch 】 | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

NOTES: (1)All parameters not specially mentioned are measured 230VAC input.

- (2)All specifications Typical @25 $^\circ\!\mathbb{C}$, unless otherwise noted, at normal line and load.
- (3)Ripple and Noise measured directly at pins/terminals at nom. load, 0.1uF bypass and 47uF electrolytic, pk-pk @20MHz bandwidth.
- (4) Specified for free-air convection cooling.
- (5)Minimum load is NOT required for proper operation .
- (6)Load regulation measured from 20% to Full load.
- (7)Line regulation measured from 100VAC to 240VAC.
- (8)Preset accuracy measured at normal load, 120VAC input.
- (9)100% Production Tested.

LinkCom Manufacturing Co., Ltd

