

GX-F/H SERIES


Related Information

■ General terms and conditions..... F-17

■ Sensor selection guide P.757~

■ Glossary of terms..... P.1386~

■ General precautions P.1405



panasonic-electric-works.net/sunx

Industry No. 1* in stable sensing

* Based on research conducted by Panasonic Electric Works SUNX as of August 2010 among equivalent rectangular inductive sensors.

Can be installed with ample space

This sensor has the longest stable sensing range among the same level of rectangular inductive proximity sensors in the industry. It is easy to install the sensor.



Type	Maximum operation distance	Stable sensing range	
		GX-F/H series	Previous model
GX-□6	1.6 mm 0.063 in	0 to 1.3 mm 0.051 in	0 to 1.2 mm 0.047 in
GX-□8	2.5 mm 0.098 in	0 to 2.1 mm 0.083 in	0 to 1.8 mm 0.709 in
GX-□12	4.0 mm 0.157 in	0 to 3.3 mm 0.130 in	0 to 3.0 mm 0.118 in
GX-□15	5.0 mm 0.197 in	0 to 4.2 mm 0.165 in	0 to 4.0 mm 0.157 in
Long sensing range	8.0 mm 0.315 in	0 to 6.7 mm 0.264 in	0 to 6.4 mm 0.252 in


* With standard sensing object

Variation at the maximum operation distance is within ±8 %

Thorough adjustment and control of sensing sensitivity greatly reduces individual sensor differences and variations.

The work of adjusting sensor positions when using multiple sensors and when sensors have been replaced is much easier.


Example: GX-□8






* Not including temperature characteristics.

Temperature characteristics vary within ±8 %

Components such as the sensor coil and core and product design have been totally revised to provide excellent temperature characteristics. Stable sensing can be obtained regardless of the time of day or the yearly season.




* Typical

APPLICATIONS**Muting control of light curtains****Positioning processing equipment****Positioning metal pallets****ENVIRONMENTAL RESISTANCE****10 times the durability! (Compared to previous models)**


The new integrated construction method used provides shock resistance of 10,000 m/s² (approx. 1,000 G in X, Y and Z directions for three times each), and vibration resistance clears durability tests of between 10 and 500 Hz (3 mm 0.118 in amplitude in X, Y and Z directions for 2 hours each). In addition, resistance to impulse noise is approx. three times greater than for previous models.

Checking up / down
operation of
compact molding
equipment



Shock resistance:
1,000 G

Sensing presence of metallic
objects on a part feeder



Vibration resistance: 500 Hz

**Highly resistant to water or oil!
IP68g* protective construction**

The new integrated construction method used improves environmental resistance performance. The IP68g prevents damage to the sensor by stopping water and oil getting inside.

* For details, refer to the "SPECIFICATIONS".

**FUNCTIONS****Indicators are easy to see over a wide field of view**

A prism with a wide field of view has greatly improved the visibility of the operation indicators.

GX-H



GX-F

**MOUNTING****Tightening strength increased with no damage! (excluding GX-□6)**

A metal sleeve has been inserted. It prevents the sensor from being damaged by tightening too much.

GX-□8, GX-□12



Approx. 1.4 times
greater than before

M3 screw
Tightening torque: 0.7 N · m or less

GX-□15



M3 screw
Tightening torque: 1 N · m or less


Conductor thickness doubled to make wiring much easier! (GX-□6/□8 only)

The conductor's thickness was doubled for the GX-□6/□8. This makes it easier to handle and perform crimping work on the cables. In addition, the tensile strength of the crimping area has become higher.

0.08 mm²
Previous model



0.15 mm²
GX-□8



Conductor thickness approx.
2 times greater

FIBER
SENSORS

LASER
SENSORS

PHOTOELECTRIC
SENSORS

MICRO
PHOTOELECTRIC
SENSORS

AREA
SENSORS

LIGHT
CURTAINS

PRESSURE /
FLOW
SENSORS

INDUCTIVE
PROXIMITY
SENSORS

PARTICULAR
USE SENSORS

SENSOR
OPTIONS

SIMPLE
WIRE-SAVING
UNITS

WIRE-SAVING
SYSTEMS

MEASUREMENT
SENSORS

STATIC CONTROL
DEVICES

ENDSCOPE

LASER
MARKERS

PLC /
TERMINALS

HUMAN MACHINE
INTERFACES

ENERGY CONSUMPTION
VISUALIZATION
COMPONENTS

view has
FA COMPONENTS

MACHINE VISION
SYSTEMS

UV CURING
SYSTEMS

Selection
Guide

Amplifier
Built-in
Amplifier-
separated

GX-F/H





GXL

GL

**GX-U/GX-FU/
GX-N**

GX

ORDER GUIDE**GX-6 type**




Type		Appearance (mm in)	Sensing range (Note 1)	Model No. (Note 2)	Output	Output operation
NPN output	Front sensing		 Maximum operation distance 1.6 mm 0.063 in (0 to 1.3 mm 0 to 0.051 in) Stable sensing range	GX-F6A	NPN open-collector transistor	Normally open
	Top sensing	GX-F6AI		Normally closed		
		GX-F6B		Normally open		
		GX-F6BI		Normally closed		
		GX-H6A		Normally open		
		GX-H6AI		Normally closed		
		GX-H6B		Normally open		
		GX-H6BI		Normally closed		
PNP output	Front sensing			GX-F6A-P	PNP open-collector transistor	Normally open
	Top sensing	GX-F6AI-P		Normally closed		
		GX-F6B-P		Normally open		
		GX-F6BI-P		Normally closed		
		GX-H6A-P		Normally open		
		GX-H6AI-P		Normally closed		
		GX-H6B-P		Normally open		
		GX-H6BI-P		Normally closed		

Notes: 1) The maximum operation distance stands for the maximum distance for which the sensor can detect the standard sensing object.

The stable sensing range stands for the sensing range for which the sensor can stably detect the standard sensing object even if there is an ambient temperature drift and/or supply voltage fluctuation.

2) "I" in the model No. indicates a different frequency type.

GX-8 type






Type		Appearance (mm in)	Sensing range (Note 1)	Model No. (Note 2)	Output	Output operation
NPN output	Front sensing		 Maximum operation distance 2.5 mm 0.098 in (0 to 2.1 mm 0 to 0.083 in) Stable sensing range	GX-F8A	NPN open-collector transistor	Normally open
	Top sensing	GX-F8AI		Normally closed		
		GX-F8B		Normally open		
		GX-F8BI		Normally closed		
		GX-H8A		Normally open		
		GX-H8AI		Normally closed		
PNP output	Front sensing			GX-F8B	PNP open-collector transistor	Normally open
	Top sensing	GX-F8BI		Normally closed		
		GX-H8A-P		Normally open		
		GX-H8AI-P		Normally closed		
		GX-H8B-P		Normally open		
		GX-H8BI-P		Normally closed		

Notes: 1) The maximum operation distance stands for the maximum distance for which the sensor can detect the standard sensing object.

The stable sensing range stands for the sensing range for which the sensor can stably detect the standard sensing object even if there is an ambient temperature drift and/or supply voltage fluctuation.

2) "I" in the model No. indicates a different frequency type.






ORDER GUIDE**GX-12 type**

Type		Appearance (mm in)	Sensing range (Note 1)	Model No. (Note 2)	Output	Output operation	
NPN output	Front sensing			GX-F12A	NPN open-collector transistor	Normally open	
	Top sensing			GX-F12AI		Normally closed	
				GX-F12B			
				GX-F12BI			
				GX-H12A			
				GX-H12AI			
PNP output	Front sensing			GX-H12B	PNP open-collector transistor	Normally open	
				GX-H12BI			
				GX-F12A-P			Normally closed
				GX-F12AI-P			
				GX-F12B-P			
	Top sensing			GX-F12BI-P		Normally open	
			GX-H12A-P				
			GX-H12AI-P				
			GX-H12B-P				
			GX-H12BI-P				

Notes: 1) The maximum operation distance stands for the maximum distance for which the sensor can detect the standard sensing object.
The stable sensing range stands for the sensing range for which the sensor can stably detect the standard sensing object even if there is an ambient temperature drift and/or supply voltage fluctuation.

2) "I" in the model No. indicates a different frequency type.

GX-15 type

Type		Appearance (mm in)	Sensing range (Note 1)	Model No. (Note 2)	Output	Output operation	
NPN output	Front sensing			GX-F15A	NPN open-collector transistor	Normally open	
	Top sensing			GX-F15AI		Normally closed	
				GX-F15B			
				GX-F15BI			
				GX-H15A			
				GX-H15AI			
PNP output	Front sensing			GX-H15B	PNP open-collector transistor	Normally open	
				GX-H15BI			Normally closed
				GX-F15A-P			
	Top sensing			GX-F15AI-P		PNP open-collector transistor	Normally open
				GX-F15B-P			
				GX-F15BI-P			
			GX-H15A-P	Normally closed			
			GX-H15AI-P				
			GX-H15B-P				
			GX-H15BI-P				

Notes: 1) The maximum operation distance stands for the maximum distance for which the sensor can detect the standard sensing object.
The stable sensing range stands for the sensing range for which the sensor can stably detect the standard sensing object even if there is an ambient temperature drift and/or supply voltage fluctuation.

2) "I" in the model No. indicates a different frequency type.






FIBER
SENSORSLASER
SENSORSPHOTO-
ELECTRIC
SENSORSMICRO
PHOTO-
ELECTRIC
SENSORSAREA
SENSORSLIGHT
CURTAINSPRESSURE /
FLOW
SENSORSINDUCTIVE
PROXIMITY
SENSORSPARTICULAR
USE
SENSORSSENSOR
OPTIONSSIMPLE
WIRE-
SAVING
UNITSWIRE-
SAVING
SYSTEMSMEASURE-
MENT
SENSORSSTATIC
CONTROL
DEVICES

ENDSCOPE

LASER
MARKERSPLC /
TERMINALSHUMAN
MACHINE
INTERFACESENERGY
CONSUMPTION
VISUALIZATION
COMPONENTSFA
COMPONENTSMACHINE
VISION
SYSTEMSUV
CURING
SYSTEMSSelection
GuideAmplifier
Built-inAmplifier
separated**GX-F/H****GXL****GL**GX-UGX-FU/
GX-N**GX**

ORDER GUIDE

GX-15 (Long sensing range) type

Type		Appearance (mm in)	Sensing range (Note 1)	Model No. (Note 2)	Output	Output operation	
NPN output	Front sensing			GX-FL15A	NPN open-collector transistor	Normally open	
		GX-FL15AI					
		GX-FL15B		Normally closed			
		GX-FL15BI					
		GX-HL15A		Normally open			
		GX-HL15AI					
Top sensing				GX-HL15B		Normally closed	
				GX-HL15BI			
PNP output	Front sensing				GX-FL15A-P	PNP open-collector transistor	Normally open
				GX-FL15AI-P			
				GX-FL15B-P	Normally closed		
				GX-FL15BI-P			
			GX-HL15A-P	Normally open			
			GX-HL15AI-P				
Top sensing			GX-HL15B-P				
			GX-HL15BI-P		Normally closed		

Notes: 1) The maximum operation distance stands for the maximum distance for which the sensor can detect the standard sensing object.
The stable sensing range stands for the sensing range for which the sensor can stably detect the standard sensing object even if there is an ambient temperature drift and/or supply voltage fluctuation.
2) "I" in the model No. indicates a different frequency type.




5 m 16.404 ft cable length type, flexible cable type


5 m 16.404 ft cable length type (standard: 1 m 3.281 ft) and flexible cable type (5 m 16.404 ft cable length type) are available. However, long sensing range type is not available. When ordering 5 m 16.404 ft cable length type, the model No. will be "GX-F15AI-P-C5" to the model No. When ordering flexible cable type, the model No. will be "GX-F15AI-P-R". (e.g.) 5 m 16.404 ft cable length type of GX-F15AI-P is "GX-F15AI-P-C5". Flexible cable type of GX-F15AI-P is "GX-F15AI-P-R".


OPTIONS

Designation	Model No.	Description
Sensor mounting bracket	MS-GX6-1	Mounting bracket for GX-6 type (recommended). Sensors can be mounted closely together for space-saving.
	MS-GL6-1	Mounting brackets for GX-6 type
	MS-GL6-2	Sensor mounting brackets for GL-6 can be used. Interchange is possible.
	MS-GXL8-4	Mounting bracket for GX-8 type
	MS-GXL15	Mounting bracket for GX-15 type
Aluminum sheet	MS-A15F	For GX-FL15□(-P)
	MS-A15H	For GX-HL15□(-P)


Sensor mounting bracket

- MS-GX6-1
 Nut is not attached.
- MS-GL6-1
 Nut is not attached.
- MS-GL6-2
 Nut is not attached.

- MS-GXL8-4
 1pc. each of M3 (length: 12 mm 0.472 in) truss head screw, nut, spring washer and plain washer is attached.

- MS-GXL15
 Nut is not attached.

Aluminum sheet

- MS-A15F
- MS-A15H


SPECIFICATIONS**GX-6 type**

Item	Model No. (Note 2)	Type	NPN output		PNP output	
		Front sensing	GX-F6A(I)	GX-F6B(I)	GX-F6A(I)-P	GX-F6B(I)-P
		Top sensing	GX-H6A(I)	GX-H6B(I)	GX-H6A(I)-P	GX-H6B(I)-P
Max. operation distance (Note 3)			1.6 mm 0.063 in ± 8 %			
Stable sensing range (Note 3)			0 to 1.3 mm 0 to 0.051 in			
Standard sensing object			Iron sheet 12 × 12 × t 1 mm 0.472 × 0.472 × t 0.039 in			
Hysteresis			20 % or less of operation distance (with standard sensing object)			
Repeatability			Along sensing axis, perpendicular to sensing axis: 0.04 mm 0.0016 in or less			
Supply voltage			12 to 24 V DC $+10\%$ -15% Ripple P-P 10 % or less			
Current consumption			15 mA or less			
Output			NPN open-collector transistor		PNP open-collector transistor	
			• Maximum sink current: 100 mA		• Maximum source current: 100 mA	
			• Applied voltage: 30 V DC or less (between output and 0 V)		• Applied voltage: 30 V DC or less (between output and 0 V)	
Utilization category			DC-12 or DC-13			
Output operation			Normally closed	Normally closed	Normally closed	Normally closed
Max. response frequency			400 Hz			
Operation indicator			Orange LED (lights up when the output is ON)			
Environmental resistance	Pollution degree		3 (Industrial environment)			
	Protection		IP68 (IEC), IP68g (JEM) (Note 4, 5)			
	Ambient temperature		− 25 to + 70 °C − 13 to + 158 °F (Storage: − 40 to + 125 °C − 40 to + 255 °F)			
	Ambient humidity		35 to 85 % RH, Storage: 35 to 95 % RH			
	EMC		EN 60947-5-2			
	Voltage withstandability		1,000 V AC for one min. between all supply terminals connected together and enclosure			
	Insulation resistance		50 MΩ, or more, with 500 V DC megger between all supply terminals and enclosure			
	Vibration resistance		10 to 500 Hz frequency, 3 mm 0.118 in amplitude (Max. 20 G) in X, Y and Z directions for two hours each			
	Shock resistance		10,000 m/s ² acceleration (1,000 G approx.) in X, Y and Z directions for three times each			
Sensing range variation	Temperature characteristics	Over ambient temperature range − 25 to + 70 °C ± 8 % of stable sensing range				
	Voltage characteristics	Within ± 2 % for $+10\%$ -15% fluctuation of the supply voltage				
Material			Enclosure: PBT, Indicator part: Polyester			
Cable			0.15 mm ² 3-core oil, heat and cold resistant cabtyre cable, 1 m 3.281 ft long			
Cable extension			Extension up to total 100 m 328.084 ft is possible with 0.3 mm ² , or more, cable.			
Net weight			15 g approx.			

Note 1) Where measurement conditions have not been specified precisely, the conditions are as follows.

2) "I" in the model No. indicates a different frequency type.

3) The maximum operation distance stands for the maximum distance for which the sensor can detect the standard sensing object.

The stable sensing range stands for the sensing range for which the sensor can stably detect the standard sensing object even if there is an ambient temperature drift and/or supply voltage fluctuation.

4) Panasonic Electric Works SUNX's IP68 test method

① Immerse at 0 m below 0 °C **+ 32 °F** water surface and leave for 30 min.

② Regard the heat shock test in ① as one cycle and perform 20 cycles.

③ Leave in water at a depth of 1 m **3.281 ft** in water for 500 hours.

④ After tests ① to ③, insulation resistance, voltage withstandability, current consumption, and sensing range must meet the standard values.

5) If using the sensor in an environment where cutting oil droplets splatter, the sensor may be deteriorated due to added substances in the oil.

FIBER
SENSORSLASER
SENSORSPHOTO-
ELECTRIC
SENSORSMICRO
PHOTO-
ELECTRIC
SENSORSAREA
SENSORSLIGHT
CURTAINSPRESSURE /
FLOW
SENSORSINDUCTIVE
PROXIMITY
SENSORSPARTICULAR
USE
SENSORSSENSOR
OPTIONSWIRE-
SAVING
SYSTEMSMEASURE-
MENT
SENSORSSTATIC
CONTROL
DEVICES

ENDSCOPE

LASER
MARKERSPLC /
TERMINALSHUMAN
MACHINE
INTERFACESENERGY
CONSUMPTION
VISUALIZATION
COMPONENTSFA
COMPONENTSIMAGE
VISION
SYSTEMSUV
CURING
SYSTEMSSelection
GuideBuilt-in
Amplifier
separated**GX-F/H****EXL**en,**GL****GX-UGX-FU/
GX-N****GX**

SPECIFICATIONS

GX-8 type

Item	Model No. (Note 2)	Type	NPN output		PNP output	
		Front sensing	GX-F8A(I)	GX-F8B(I)	GX-F8A(I)-P	GX-F8B(I)-P
		Top sensing	GX-H8A(I)	GX-H8B(I)	GX-H8A(I)-P	GX-H8B(I)-P
Max. operation distance (Note 3)			2.5 mm 0.098 in ± 8 %			
Stable sensing range (Note 3)			0 to 2.1 mm 0 to 0.083 in			
Standard sensing object			Iron sheet 15 × 15 × t 1 mm 0.591 × 0.591 × t 0.039 in			
Hysteresis			20 % or less of operation distance (with standard sensing object)			
Repeatability			Along sensing axis, perpendicular to sensing axis: 0.04 mm 0.0016 in or less			
Supply voltage			12 to 24 V DC $\begin{smallmatrix} +1 \\ -15 \end{smallmatrix} 0\%$ Ripple P-P 10 % or less			
Current consumption			15 mA or less			
Output			NPN open-collector transistor		PNP open-collector transistor	
			• Maximum sink current: 100 mA		• Maximum source current: 100 mA	
			• Applied voltage: 30 V DC		or • Applied voltage: 30 V DC	
			• Residual voltage: (at 100 mA)		• Residual voltage: (at 100 mA)	
Utilization category			DC-12 or DC-13			
Output operation			Normally open	Normally closed	Normally open	Normally closed
Max. response frequency			500 Hz			
Operation indicator			Orange LED (lights up when the output is ON)			
Environmental resistance	Pollution degree		3 (Industrial environment)			
	Protection		IP68 (IEC), IP68g (JEM) (Note 4, 5)			
	Ambient temperature		− 2 5 t o + 7 0 ° C − 1 3 t o + 1 5 8 ° F Storage: − 1 8 ° C + 7 0 ° C			
	Ambient humidity		35 to 85 % RH, Storage: 35 to 95 % RH			
	EMC		EN 60947-5-2			
	Voltage withstandability		1,000 V AC for one min. between all supply terminals connected together and enclosure			
	Insulation resistance		5 0 M Ω , o r m o r e , w i t h 5 0 0 V D C m e g g e r b e t w e e n a l l s u p p l y t e r m i n a l s a n d e n c l o s u r e			
	Vibration resistance		10 to 500 Hz frequency, 3 mm 0.118 in amplitude (Max. 20 G) in X, Y and Z directions for two hours each			
	Shock resistance		10,000 m/s ² acceleration (1,000 G approx.) in X, Y and Z directions for three times each			
Sensing range variation	Temperature characteristics		Over ambient temperature range − 1 3 t o + 1 5 8 ° F ± 8 % o f s e n s i n g r a n g e			
	Voltage characteristics		Within ±2 % for $\begin{smallmatrix} +1 \\ -15 \end{smallmatrix} 0\%$ fluctuation of the supply voltage			
Material			Enclosure: PBT, Indicator part: Polyester			
Cable			0.15 mm ² 3-core oil, heat and cold resistant cabtyre cable, 1 m 3.281 ft long			
Cable extension			Extension up to total 100 m 328.084 ft is possible with 0.3 mm ² , or more, cable.			
Net weight			Front sensing type: 15 g approx., Top sensing type: 20 g approx..			

- Note 4) Where measurement conditions have not been specified precisely, the conditions are as follows.
- 1) "I" in the model No. indicates a different frequency type.
 - 2) "I" in the model No. indicates a different frequency type.
 - 3) The maximum operation distance stands for the maximum distance for which the sensor can detect the standard sensing object.
The stable sensing range stands for the sensing range for which the sensor can stably detect the standard sensing object even if there is an ambient temperature drift and/or supply voltage fluctuation.
 - 4) Panasonic Electric Works SUNX's IP68 test method
 - ① Immerse at 0 m below 0 °C + 32 °F water surface and leave for 30 min. Then,
 - ② Regard the heat shock test in ① as one cycle and perform 20 cycles.
 - ③ Leave in water at a depth of 1 m 3.281 ft in water for 500 hours.
 - ④ After tests ① to ③, insulation resistance, voltage withstandability, current consumption, and sensing ranges must meet the standard values.
 - 5) If using the sensor in an environment where cutting oil droplets splatter, the sensor may deteriorate due to added substances in the oil.

SPECIFICATIONS**GX-12 type**

Item	Model No. (Note 2)	Type	NPN output		PNP output			
		Front sensing	GX-F12A(I)	GX-F12B(I)	GX-F12A(I)-P	GX-F12B(I)-P		
		Top sensing	GX-H12A(I)	GX-H12B(I)	GX-H12A(I)-P	GX-H12B(I)-P		
		Max. operation distance (Note 3)	4.0 mm 0.157 in ± 8 %					AREA SENSORS
		Stable sensing range (Note 3)	0 to 3.3 mm 0 to 0.130 in					LIGHT CURTAINS
		Standard sensing object	Iron sheet 20 × 20 × t 1 mm 0.787 × 0.787 × t 0.039 in					PRESSURE / FLOW SENSORS
		Hysteresis	20 % or less of operation distance (with standard sensing object)					INDUCTIVE PROXIMITY SENSORS
		Repeatability	Along sensing axis, perpendicular to sensing axis: 0.04 mm 0.0016 in or less					
		Supply voltage	12 to 24 V DC $+10\%$ -15% Ripple P-P 10 % or less					PARTICULAR USE SENSORS
		Current consumption	15 mA or less					SENSOR OPTIONS
Output		NPN open-collector transistor			PNP open-collector transistor			WIRE- SAVING UNIVERSAL S
		• Maximum sink current: 100 mA			• Maximum source current: 100 mA			
		• Applied voltage: 30 V DC or less (between output and 0 V)			• Applied voltage: 30 V DC or less (between output and 0 V)			
		Utilization category	DC-12 or DC-13					WIRE- SAVING SYSTEMS
		Output operation	Normally open	Normally closed	Normally open	Normally closed	MEASURE- MENT SENSORS	
		Max. response frequency	500 Hz					STATIC CONTROL DEVICES
		Operation indicator	Orange LED (lights up when the output is ON)					ENDSCOPE
Environmental resistance		Pollution degree	3 (Industrial environment)					LASER MARKERS
		Protection	IP68 (IEC), IP68g (JEM) (Note 4, 5)					PLC / TERMINALS
		Ambient temperature	− 25 to + 70 °C − 13 to + 158 °F, Storage: − 15 to + 85 °F					HUMAN MACHINE INTERFACES
		Ambient humidity	35 to 85 % RH, Storage: 35 to 95 % RH					ENERGY CONSUMPTION VISUALIZATION COMPONENTS
		EMC	EN 60947-5-2					FA COMPONENTS
		Voltage withstandability	1,000 V AC for one min. between all supply terminals connected together and enclosure					MACHINE VISION SYSTEMS
		Insulation resistance	50 MΩ, or more, with 500 V DC megger between all supply terminals					UV CURING SYSTEMS
		Vibration resistance	10 to 500 Hz frequency, 3 mm 0.118 in amplitude (Max. 20 G) in X, Y and Z directions for two hours each					
	Shock resistance	10,000 m/s ² acceleration (1,000 G approx.) in X, Y and Z directions for three times each						
Sensing range variation	Temperature characteristics	Over ambient temperature range − 25 to + 70 °C ± 8 % of sensing range						
	Voltage characteristics	Within ± 2 % for $+10\%$ -15% fluctuation of the supply voltage						
		Material	Enclosure: PBT, Indicator part: Polyester					
		Cable	0.15 mm ² 3-core oil, heat and cold resistant cabtyre cable, 1 m 3.281 ft long					
		Cable extension	Extension up to total 100 m 328.084 ft is possible with 0.3 mm ² , or more, cable.					
		Net weight	Front sensing type: 20 g approx., Top sensing type: 20 g approx..					Selection Guide

Note 1) Where measurement conditions have not been specified precisely, the conditions are as follows.

2) "I" in the model No. indicates a different frequency type.

3) The maximum operation distance stands for the maximum distance for which the sensor can detect the standard sensing object.

The stable sensing range stands for the sensing range for which the sensor can stably detect the standard sensing object even if there is an ambient temperature drift and/or supply voltage fluctuation.

4) Panasonic Electric Works SUNX's IP68 test method

① Immerse at 0 m below 0 °C **+ 32 °F** water surface and leave for 30 min.

② Regard the heat shock test in ① as one cycle and perform 20 cycles.

③ Leave in water at a depth of 1 m **3.281 ft** in water for 500 hours.

④ After tests ① to ③, insulation resistance, voltage withstandability, current consumption, and sensing ranges must meet the standard values.

5) If using the sensor in an environment where cutting oil droplets splatter, the sensor may deteriorate due to added substances in the oil.

FIBER SENSORS

LASER SENSORS

PHOTO-ELECTRIC SENSORS

MICRO PHOTO-ELECTRIC SENSORS

AREA SENSORS

LIGHT CURTAINS

PRESSURE / FLOW SENSORS

INDUCTIVE PROXIMITY SENSORS

PARTICULAR USE SENSORS

SENSOR OPTIONS

WIRE-SAVING SYSTEMS

MEASURE-MENT SENSORS

STATIC CONTROL DEVICES

ENDSCOPE

LASER MARKERS

PLC / TERMINALS

HUMAN MACHINE INTERFACES

ENERGY CONSUMPTION VISUALIZATION COMPONENTS

FA COMPONENTS

MACHINE VISION SYSTEMS

UV CURING SYSTEMS

Selection Guide

Built-in Amplifier separated

GX-F/H

GX-L

GX-N

GX-N

GX-N

GX-N

GX-N

GX-N

GX-N


SPECIFICATIONS

GX-15 type

		Type	NPN output				PNP output			
			Long sensing range				Long sensing range			
Item	Model No. (Note 2)	Front sensing	GX-F15A(I)	GX-F15B(I)	GX-FL15A(I)	GX-FL15B(I)	GX-F15A(I)-P	GX-F15B(I)-P	GX-FL15A(I)-P	GX-FL15B(I)-P
		Top sensing	GX-H15A(I)	GX-H15B(I)	GX-HL15A(I)	GX-HL15B(I)	GX-H15A(I)-P	GX-H15B(I)-P	GX-HL15A(I)-P	GX-HL15B(I)-P
Max. operation distance (Note 3)			5.0 mm 0.197 in ± 8 %		8.0 mm 0.315 in ± 8 % (Note 4)		5.0 mm 0.197 in ± 8 %		8.0 mm 0.315 in ± 8 % (Note 4)	
Stable sensing range (Note 3)			0 to 4.2 mm 0 to 0.165 in		0 to 6.7 mm 0 to 0.264 in (Note 4)		0 to 4.2 mm 0 to 0.165 in		0 to 6.7 mm 0 to 0.264 in (Note 4)	
Standard sensing object			Iron sheet 20 × 20 × t 1 mm 0.7874 × 0.7874 × t 0.039 in		Iron sheet 30 × 30 × t 1 mm 1.181 × 1.181 × t 0.039 in		Iron sheet 20 × 20 × t 1 mm 0.7874 × 0.7874 × t 0.039 in		Iron sheet 30 × 30 × t 1 mm 1.181 × 1.181 × t 0.039 in	
Hysteresis			20 % or less of operation distance (with standard sensing object)							
Repeatability			Along sensing axis, perpendicular to sensing axis: 0.04 mm 0.0016 in or less							
Supply voltage			12 to 24 V DC $\pm \frac{1}{15} \%$ Ripple P-P 10 % or less							
Current consumption			15 mA or less							
Output			NPN open-collector transistor				PNP open-collector transistor			
			• Maximum sink current : 100 mA				• Maximum source current : 100 mA			
			• Applied voltage : 30 V DC or less (between output and 0 V) less				• Applied voltage : 30 V DC or less (between output and 0 V) less			
Utilization category			DC-12 or DC-13							
Output operation			Normally open	Normally closed	Normally open	Normally closed	Normally open	Normally closed	Normally open	Normally closed
Max. response frequency			250 Hz		150 Hz (Note 5)		250 Hz		150 Hz (Note 5)	
Operation indicator			Orange LED (lights up when the output is ON)							
Environmental resistance	Pollution degree		3 (Industrial environment)							
	Protection		IP68 (IEC), IP68g (JEM) (Note 6, 7)							
	Ambient temperature		− 2 5 t o + 7 0 ° C − 1 3 t o + 1 5 8 ° F , Storage : − 1 8 5 ° F							
	Ambient humidity		35 to 85 % RH, Storage: 35 to 95 % RH							
	EMC		EN 60947-5-2							
	Voltage withstandability		1,000 V AC for one min. between all supply terminals connected together and enclosure							
	Insulation resistance		5 0 M Ω , or more , with 5 0 0 V DC megger between all supply terminals and enclosure							
	Vibration resistance		10 to 500 Hz frequency, 3 mm 0.118 in amplitude (Max. 20 G) in X, Y and Z directions for two hours each							
Shock resistance			10,000 m/s ² acceleration (1,000 G approx.) in X, Y and Z directions for three times each							
Sensing range variation	Temperature characteristics		Over ambient temperature range − 2 5 t o + 7 0 ° C − 1 3 t o + 1 5 8 ° F , within ± 8 % of sensing range							
	Voltage characteristics		Within ± 2 % for $\pm \frac{1}{15} \%$ fluctuation of the supply voltage							
Material			Enclosure: PBT, Indicator part: Polyester							
Cable			0.15 mm ² 3-core oil, heat and cold resistant cabtyre cable, 1 m 3.281 ft long							
Cable extension			Extension up to total 100 m 328.084 ft is possible with 0.3 mm ² , or more, cable.							
Net weight			20 g approx.							



Note 1) When measurement conditions have not been specified precisely, the conditions are as follows.

- 2) "I" in the model No. indicates a different frequency type.
- 3) The maximum operation distance stands for the maximum distance for which the sensor can detect the standard sensing object.
The stable sensing range stands for the sensing range for which the sensor can stably detect the standard sensing object even if there is an ambient temperature drift and/or supply voltage fluctuation.
- 4) This is the numerical value which the sensor mount onto an insulant plate. When mounted onto a steel or stainless steel plate, insert the optional aluminum sheet between the sensor and the plate.
- 5) This is the numerical value which the sensor mount onto an insulant plate. When mounted onto a metallic plate, max. response frequency will decrease.
- 6) Panasonic Electric Works SUNX's IP68 test method
 - ① Immerse at 0 m below 0 °C + 32 °F water surface and leave for 30 min. Then,
 - ② Regard the heat shock test in ① as one cycle and perform 20 cycles.
 - ③ Leave in water at a depth of 1 m 3.281 ft in water for 500 hours.
 - ④ After tests ① to ③, insulation resistance, voltage withstandability, current consumption, and sensing range must meet the standard values.
- 7) If using the sensor in an environment where cutting oil droplets splatter, the sensor may be deteriorated due to added substances in the oil.

I/O CIRCUIT DIAGRAMS**NPN output type****I/O circuit diagram**


Symbols ... D1: Reverse supply polarity protection diode
D2: Reverse output polarity protection diode
ZD: Surge absorption zener diode
Tr : NPN output transistor

Note: The output does not incorporate a short-circuit protection circuit.
Do not connect it directly to a power supply or a capacitive load.

Wiring diagram**PNP output type****I/O circuit diagram**

Symbols ... D1: Reverse supply polarity protection diode
D2: Reverse output polarity protection diode
ZD: Surge absorption zener diode
Tr : PNP output transistor

Note: The output does not incorporate a short-circuit protection circuit.
Do not connect it directly to a power supply or a capacitive load.

Wiring diagramFIBER
SENSORSLASER
SENSORSPHOTO-
ELECTRIC
SENSORSMICRO
PHOTO-
ELECTRIC
SENSORSAREA
SENSORSLIGHT
CURTAINSPRESSURE /
FLOW
SENSORS**INDUCTIVE
PROXIMITY
SENSORS**PARTICULAR
USE
SENSORSSENSOR
OPTIONSSIMPLE
WIRE-
SAVING
UNITSWIRE-
SAVING
SYSTEMSMEASURE-
MENT
SENSORSSTATIC
CONTROL
DEVICES

ENDOSCOPE


LASER
MARKERSPLC /
TERMINALSHUMAN
MACHINE
INTERFACESENERGY
CONSUMPTION
VISUALIZATION
COMPONENTSFA
COMPONENTSMACHINE
VISION
SYSTEMSUV
CURING
SYSTEMSSelection
GuideAmplifier
Built-inAmplifier
separated**GX-F/H****GXL****GL**GX-UGX-FU/
GX-N**GX**

FIBER SENSORS
LASER SENSORS
PHOTO-ELECTRIC SENSORS
MICRO PHOTO-ELECTRIC SENSORS
AREA SENSORS
LIGHT CURTAINS
PRESSURE / FLOW SENSORS
INDUCTIVE PROXIMITY SENSORS
PARTICULAR USE SENSORS
SENSOR OPTIONS
SIMPLE WIRE-SAVING UNITS
WIRE-SAVING SYSTEMS
MEASURE-MENT SENSORS
STATIC CONTROL DEVICES
ENDOSCOPE
LASER MARKERS
PLC / TERMINALS
HUMAN MACHINE INTERFACES
ENERGY CONSUMPTION VISUALIZATION COMPONENTS
FA COMPONENTS
MACHINE VISION SYSTEMS
UV CURING SYSTEMS
Selection Guide
A m p I Built-in
A m p I separated
GX-F/H
GXL
GL
GX-UGX-F/H GX-N
GX


SENSING CHARACTERISTICS (TYPICAL)

GX-6 type

Sensing field




Correlation between sensing object size and sensing range




As the sensing object size becomes smaller than the standard size (iron sheet $12 \times 12 \times 1$ mm $0.472 \times 0.472 \times 0.039$ in), the sensing range shortens as shown in the left figure.

GX-8 type

Sensing field




Correlation between sensing object size and sensing range




As the sensing object size becomes smaller than the standard size (iron sheet $15 \times 15 \times 1$ mm $0.591 \times 0.591 \times 0.039$ in), the sensing range shortens as shown in the left figure.

GX-12 type

Sensing field




Correlation between sensing object size and sensing range




As the sensing object size becomes smaller than the standard size (iron sheet $20 \times 20 \times 1$ mm $0.787 \times 0.787 \times 0.039$ in), the sensing range shortens as shown in the left figure.

GX-15 type



Sensing field



Correlation between sensing object size and sensing range



As the sensing object size becomes smaller than the standard size (iron sheet $20 \times 20 \times 1$ mm $0.787 \times 0.787 \times 0.039$ in), the sensing range shortens as shown in the left figure.

SENSING CHARACTERISTICS (TYPICAL)**GX-15 (Long sensing range) type****Sensing field****Correlation between sensing object size and sensing range**

As the sensing object size becomes smaller than the standard size (iron sheet 30 × 30 × t 1 mm 1.181 × 1.181 × t 0.039 in), the sensing range shortens as shown in the left figure.

PRECAUTIONS FOR PROPER USE

Refer to General precautions.




- Never use this product as a sensing device for personnel protection.
- In case of using sensing devices for personnel protection, use products which meet laws and standards, such as OSHA, ANSI or IEC etc., for personnel protection applicable in each region or country.

Mounting**GX-6 type**


- Use the optional sensor mounting bracket when installing.

<When using MS-GX6-1 (recommended)>


- To mount the sensor with a nut, the mounting hole diameter should be $\phi 3.4$ mm $\phi 0.134$ in.
- ① Insert the sensor into the bracket as shown on the right.
 - ② Push the sensor until the bracket hook is lodged in the groove on the upper portion of the sensor.
 - ③ Fix the bracket in place with M3 pan head screw.

**<When using MS-GL6-1 / MS-GL6-2>**


- To mount the sensor with a nut, the mounting hole diameter should be $\phi 3.4$ mm $\phi 0.134$ in.

**GX-8 type**


- Make sure to use a M3 (length: 12 mm 0.472 in or more) truss head screw. The tightening torque should be 0.7 N·m or less. (Do not use a screw or a pan head screw.)

**GX-12 type**


- The tightening torque should be 0.7 N·m or less.
- To mount the sensor with a nut, the mounting hole diameter should be $\phi 3.4$ mm $\phi 0.134$ in. Further, the hole in which the boss is inserted should be $\phi 2.5$ mm $\phi 0.098$ in and 3 mm 0.118 in, or more, deep.

**GX-15 type**

- The tightening torque should be 1 N·m or less.
- To mount the sensor with a nut, the mounting hole diameter should be $\phi 3.4$ mm $\phi 0.134$ in.



- When installing the long sensing range type on iron or stainless steel plate, put the optional aluminum sheet in between the sensor and the plate.



FIBER SENSORS

LASER SENSORS

PHOTO-ELECTRIC SENSORS

MICRO PHOTO-ELECTRIC SENSORS

AREA SENSORS

LIGHT CURTAINS

PRESSURE / FLOW SENSORS

INDUCTIVE PROXIMITY SENSORS

PARTICULAR USE SENSORS

SENSOR OPTIONS

SIMPLE WIRE-SAVING UNITS

WIRE-SAVING SYSTEMS

MEASURE-MENT SENSORS

STATIC CONTROL DEVICES

ENDOSCOPE

LASER MARKERS

PLC / TERMINALS

HUMAN MACHINE INTERFACES

ENERGY CONSUMPTION VISUALIZATION COMPONENTS

FA COMPONENTS

MACHINE VISION SYSTEMS

UV CURING SYSTEMS

Selection Guide

Amplifier Built-in

Amplifier separated

GX-F/H

GXL

GL

GX-UGX-FU/ GX-N


GX

PRECAUTIONS FOR PROPER USE

Refer to General precautions.


Influence of surrounding metal

- When there is a metal near the sensor, keep the minimum separation distance specified below.

Front sensing type

	GX-F6 type	GX-F8 type	GX-F12 type	GX-F15 type	GX-FL15 type
A	6 mm 0.236 in (Note 1)	7.4 mm 0.291 in	7.1 mm 0.280 in	8 mm 0.315 in	8 mm 0.315 in (Note 2)
B	8 mm 0.315 in	8 mm 0.315 in	20 mm 0.787 in	20 mm 0.787 in	30 mm 1.181 in
C	3 mm 0.118 in	3 mm 0.118 in	7 mm 0.276 in	7 mm 0.276 in	10 mm 0.394 in

Notes: 1) When using **MS-GX6-1** (recommended mounting bracket), the distance "A" including the thickness of mounting bracket will be 6.4 mm **0.252 in**.
 2) The **GXL-FL15** type should be mounted on an insulator. To mount it on an iron or stainless steel, use the enclosed aluminum sheet.

Top sensing type

	GX-H6 type	GX-H8 type	GX-H12 type	GX-H15 type	GX-HL15 type
D	3 mm 0.118 in	4 mm 0.157 in	7 mm 0.276 in	6 mm 0.236 in	12 mm 0.472 in
E	10 mm 0.394 in	10 mm 0.394 in	20 mm 0.787 in	20 mm 0.787 in	30 mm 1.181 in
F	2 mm 0.079 in	3 mm 0.118 in	3 mm 0.118 in	0 mm 0 in	10 mm 0.394 in (Note)
G	2 mm 0.079 in	3 mm 0.118 in	3 mm 0.118 in	3 mm 0.118 in	10 mm 0.394 in

Note: When **GX-HL15** type is mounted on an insulator or seated on the enclosed aluminum sheet, the distance "F" can be zero.

Mutual interference prevention

- When two or more sensors are installed in parallel or face to face, keep the minimum separation distance specified below to avoid mutual interference.

	H	J
GX-F6 GX-H6 type	Between "I" type and non "I" type (Note 2)	0 mm 0.591 in
	Between two "I" types or two non "I" types	13 mm 0.512 in
GX-F8 GX-H8 type	Between "I" type and non "I" type (Note 2)	0 mm 0.591 in
	Between two "I" types or two non "I" types	20 mm 0.787 in
GX-F12 GX-H12 type	Between "I" type and non "I" type (Note 2)	0 mm 0.984 in
	Between two "I" types or two non "I" types	25 mm 0.984 in
GX-F15 GX-H15 type	Between "I" type and non "I" type (Note 2)	0 mm 0.984 in
	Between two "I" types or two non "I" types	45 mm 1.772 in
GX-FL15 GX-HL15 type	Between "I" type and non "I" type (Note 2)	0 mm 0.984 in
	Between two "I" types or two non "I" types	110 mm 3.059 in

Notes: 1) "I" in the model No. specifies the different frequency type.

- 2) Close mounting is possible for up to two sensors. When mounting three sensors or more at an equal spacing, align the model with "I" and the model without "I" alternately. The minimum value of dimension "H" should be as given below.

GX-F6 / H6 type: 3.5mm **0.138 in**
GX-F8 / H8 type: 6mm **0.236 in**
GX-F12 / H12 type: 6.5mm **0.256 in**
GX-F15 / H15 type: 15mm **0.591 in**
GX-FL15 / HL15 type: 47.5mm **1.870 in**

Sensing range

- The sensing range is specified for a sensing object with a non-ferrous metal, the sensing range is obtained by multiplying with the specified below. Further, the sensing range is specified below. Further, the sensing range is specified below.

Correction coefficient



Model No.	GX-F6 GX-H6 type	GX-F8 GX-H8 type	GX-F12 GX-H12 type	GX-F15 GX-H15 type	GX-FL15 type	GX-HL15 type
Metal						
Iron	1	1	1	1	1	1
Stainless steel (SUS304)	0.76 approx.	0.76 approx.	0.79 approx.	0.68 approx.	0.70 approx.	0.76 approx.
Brass	0.50 approx.	0.50 approx.	0.56 approx.	0.47 approx.	0.45 approx.	0.50 approx.
Aluminum	0.48 approx.	0.48 approx.	0.53 approx.	0.45 approx.	0.43 approx.	0.48 approx.

Wiring

- The output does not incorporate a short-circuit protection circuit. Do not connect it directly to a power supply or a capacitive load.

Others

- Do not use during the initial transient time (50 ms) after the power supply is switched on.


Front sensing**Top sensing**

DIMENSIONS (Unit: mm in)


The CAD data in the dimensions can be downloaded from our website.

GX-F6 □


Sensor

**GX-H6** □


Sensor

**GX-F8** □


Sensor

**GX-H8** □


Sensor

**GX-F12** □


Sensor

**GX-H12** □


Sensor

**GX-F(L)15** □

Sensor

**GX-H(L)15** □

Sensor

FIBER
SENSORSLASER
SENSORSPHOTO-
ELECTRIC
SENSORSMICRO
PHOTO-
ELECTRIC
SENSORSAREA
SENSORSLIGHT
CURTAINSPRESSURE /
FLOW
SENSORSINDUCTIVE
PROXIMITY
SENSORSPARTICULAR
USE
SENSORSSENSOR
OPTIONSSIMPLE
WIRE-SAVING
UNITSWIRE-SAVING
SYSTEMSMEASURE-
MENT
SENSORSSTATIC
CONTROL
DEVICES


ENDOSCOPE

LASER
MARKERSPLC/
TERMINALSHUMAN
MACHINE
INTERFACESENERGY
CONSUMPTION
VISUALIZATION
COMPONENTSFA
COMPONENTSMACHINE
VISION
SYSTEMSUV
CURING
SYSTEMSSelection
GuideAmplifier
Built-inAmplifier
Separated**GX-F/H****GXL****GL**GX-UGX-FU/
GX-N**GX**


DIMENSIONS (Unit: mm in)

The CAD data in the dimensions can be downloaded from our website.

MS-GX6-1	Sensor mounting bracket for GX-6 type (Optional)
-----------------	---




MS-GL6-1 Sensor mounting bracket for **GX-6** type (Optional)




Note: 20 mm **0.787 in** w i t h t h e s e n s o r f t

MS-GL6-2	Sensor mounting bracket for GX-6 type (Optional)
-----------------	---



Note: 13.4 mm **0.528 in** w i t h t h e s e n


MS-GXL8-4 Sensor mounting bracket for **GX-8** type (Optional)



Material: Stainless steel (SUS304)


1 pc. each of M3 (length 12 mm 0.472 in) truss head screw, nut, spring washer and plain washer is attached.

MS-GXL15	Sensor mounting bracket for GX-15 type (Optional)
-----------------	--



Material: SPCC

MS-A15F	MS-A15H	Aluminum sheet (Optional)
---------	---------	---------------------------



FIBER SENSORS	
LASER SENSORS	
PHOTO-ELECTRIC SENSORS	
MICRO PHOTO-ELECTRIC SENSORS	
AREA SENSORS	
LIGHT CURTAINS	
PRESSURE / FLOW SENSORS	
INDUCTIVE PROXIMITY SENSORS	
PARTICULAR USE SENSORS	
SENSOR OPTIONS	
SIMPLE WIRE-SAVING UNITS	
WIRE-SAVING SYSTEMS	
MEASURE-MENT SENSORS	
STATIC CONTROL DEVICES	
ENDOSCOPE	
LASER MARKERS	
PLC / TERMINALS	
HUMAN MACHINE INTERFACES	
ENERGY CONSUMPTION VISUALIZATION COMPONENTS	
FA COMPONENTS	
MACHINE VISION SYSTEMS	
UV CURING SYSTEMS	
Selection Guide	
A m p l Built-in	
A m p l separated	
GX-F/H	
GXL	
GL	
GX-UGX-F/H GX-N	
GX	

MEMO