HUBER+SUHNER® DATA SHEETCoaxial Cable Connector: 16 QMA-W50-2-10/133 N



Description

Right angle cable plug

Interface Standards
QMA IP 68 rated - QLF compliant

Technical Data Electrical Data

 $\begin{array}{ll} \text{Impedance} & 50~\Omega \\ \text{Interface frequency max.} & 18~\text{GHz} \end{array}$

Mechanical Data

Centre contact soldered
Outer contact crimped

Environmental Data

Operating Temperature -40 °C to 105 °C 2002/95/EC (RoHS) compliant

Material Data

Piece PartsMaterialSurface PlatingCentre contactBrassSUCOPRO PlatingOuter contactBrassSUCOPLATE (R) PlatingBodyBrassSUCOPLATE (R) PlatingInsulatorPTFE

Gasket MVQ (Silicone Rubber)

Crimp ferrule Copper SUCOPLATE (R) Plating

Related Documents

Outline drawing DOU-00121598
Assembly instruction DOC-0000312747

Ordering Information

Bulk 100 pcs package 16_QMA-W50-2-10/133_NH

Additional Information

Suitable cables ENVIROFLEX_316, RG_174_/U, RG_316_/U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions

HUBER+SUHNER
HUBER+SUHNER AG

RF Technology 9100 Herisau, Switzerland Phone +41 (0)71 353 41 11 Fax +41 (0)71 353 45 90 www.hubersuhner.com

Document: DOC-0000332957 C Issued: 21.06.10 Uncontrolled Copy Page 1/1