

Pin Definition:
 1. Base
 2. Collector
 3. Emitter

TSC128D

High Voltage NPN Transistor with Diode

PRODUCT SUMMARY

BV_{CBO}	400V
BV_{CES}	700V
I_C	4A
V_{CE(SAT)}	1.5V @ I _C / I _B = 4A / 1A

Features

- Build-in Free-wheeling Diode Makes Efficient Anti-saturation Operation
- No Need to Interest an hfe Value Because of Low Variable Storage-time Spread Even Though Comer Spirit Product.
- Low Base Drive Requirement
- Suitable for Half Bridge Light Ballast Application

Structure

- Silicon Triple Diffused Type
- NPN Silicon Transistor
- Integrated Anti-parallel Collector-Emitter Diode


Ordering Information

Part No.	Package	Packing
TSC128DCZ C0	TO-220	50pcs / Tube
TSC128DCM RN	TO-263	800pcs / 13" Reel

Absolute Maximum Rating (Ta = 25°C unless otherwise noted)

Parameter	Symbol	Limit	Unit
Collector-Base Voltage	V _{CBO}	700	V
Collector-Emitter Voltage @ V _{BE} =0V	V _{CES}	700	V
Collector-Emitter Voltage	V _{CEO}	400	V
Emitter-Base Voltage	V _{EBO}	9	V
Collector Current	I _C	4	A
Collector Peak Current (tp <5ms)	I _{CM}	8	A
Base Current	I _B	2	A
Base Peak Current (tp <5ms)	I _{BM}	4	A
Power Total Dissipation @ T _c =25°C	P _{DTOT}	35	W
Maximum Operating Junction Temperature	T _J	+150	°C
Storage Temperature Range	T _{STG}	-55 to +150	°C

Block Diagram



Thermal Performance

Parameter		Symbol	Limit	Unit
Thermal Resistance - Junction to Case	TO-220	$R\Theta_{JC}$	1.78	$^{\circ}\text{C}/\text{W}$
	TO-263		1.78	
Thermal Resistance - Junction to Ambient	TO-220	$R\Theta_{JA}$	62.5	$^{\circ}\text{C}/\text{W}$
	TO-263		62.5	

Electrical Specifications (Ta = 25°C unless otherwise noted)

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Static						
Collector-Base Voltage	$I_C=1\text{mA}, I_B=0$	BV_{CBO}	700	--	--	V
Collector-Emitter Breakdown Voltage	$I_C=10\text{mA}, I_E=0$	BV_{CEO}	400	--	--	V
Emitter-Base Breakdown Voltage	$I_E=1\text{mA}, I_C=0$	BV_{EBO}	9	--	--	V
Collector Cutoff Current	$V_{CB}=700\text{V}, I_E=0$	I_{CBO}	--	--	100	uA
Collector Cutoff Current	$V_{CE}=400\text{V}, I_B=0$	I_{CEO}	--	--	250	uA
Emitter Cutoff Current	$V_{EB}=7\text{V}, I_C=0$	I_{EBO}	--	--	10	uA
Collector-Emitter Saturation Voltage	$I_C=0.5\text{A}, I_B=0.1\text{A}$	$V_{CE(SAT)1}$	--	0.25	0.7	V
	$I_C=1\text{A}, I_B=0.2\text{A}$	$V_{CE(SAT)2}$	--	0.5	1	
	$I_C=2.5\text{A}, I_B=0.5\text{A}$	$V_{CE(SAT)3}$	--	1.2	1.5	
	$I_C=4\text{A}, I_B=1\text{A}$	$V_{CE(SAT)4}$	--	0.5	--	
Base-Emitter Saturation Voltage	$I_C=1\text{A}, I_B=0.2\text{A}$	$V_{BE(SAT)1}$	--	--	1.1	V
	$I_C=2\text{A}, I_B=0.5\text{A}$	$V_{BE(SAT)2}$	--	--	1.2	
DC Current Gain	$V_{CE}=5\text{V}, I_C=10\text{mA}$	Hfe	10	--	--	
	$V_{CE}=5\text{V}, I_C=1\text{A}$		17	--	27	
	$V_{CE}=5\text{V}, I_C=2\text{A}$		12	--	32	
Forward Voltage Drop	$I_F=2\text{A}$	V_f	--	--	2	V
Turn On Time	$V_{CC}=250\text{V}, I_C=1\text{A}, I_{B1}=I_{B2}=0.2\text{A}, t_p=25\mu\text{s}$	t_{ON}	--	0.2	0.6	uS
Storage Time		t_{STG}	--	3.0	4.5	uS
Fall Time		t_f	--	0.2	0.3	uS

Notes: Pulsed duration =380uS, duty cycle ≤2%

Electrical Characteristics Curve ($T_a = 25^\circ\text{C}$, unless otherwise noted)

Figure 1. Static Characteristics




Figure 3. $V_{ce(\text{sat})}$ v.s. $V_{be(\text{sat})}$




Figure 5. Reverse Bias SOA




Figure 2. DC Current Gain




Figure 4. Power Derating






Figure 6. Safety Operating Area




TO-220 Mechanical Drawing




TO-220 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	9.31	10.550	0.366	0.415
B	3.740	3.910	0.147	0.154
C	2.440	2.940	0.096	0.116
D	2.22	3.22	0.087	0.127
E	0.78	0.98	0.030	0.038
F	2.34	2.65	0.092	0.104
G	4.69	5.31	0.184	0.209
H	12.32	13.88	0.485	0.546
I	8.74	9.26	0.344	0.364
J	15.07	16.07	0.593	0.632
K	4.35	4.65	0.171	0.183
L	1.16	1.40	0.045	0.055
M	27.39	30.35	1.078	1.194
N	1.785	2.675	0.070	0.105
O	1.50	1.75	0.059	0.068
P	5.75	7.65	0.226	0.301

Marking Diagram




Y = Year Code
M = Month Code
 (A=Jan, B=Feb, C=Mar, D=Apl, E=May, F=Jun, G=Jul, H=Aug,
 I=Sep, J=Oct, K=Nov, L=Dec)
L = Lot Code

TO-263 Mechanical Drawing



TO-263 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	10.000	10.500	0.394	0.413
B	14.605	15.875	0.575	0.625
C	0.508	0.991	0.020	0.039
D	2.420	2.660	0.095	0.105
E	4.064	4.830	0.160	0.190
F	1.118	1.400	0.045	0.055
G	0.450	0.730	0.018	0.029
H	8.280	8.800	0.325	0.346
I	1.140	1.400	0.044	0.055
J	1.480	1.520	0.058	0.060

Marking Diagram



Y = Year Code
M = Month Code
 (A=Jan, B=Feb, C=Mar, D=Apl, E=May, F=Jun, G=Jul, H=Aug,
 I=Sep, J=Oct, K=Nov, L=Dec)
L = Lot Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.