



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Vss	Vcc	Vo	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	A	K

- NOTES:
- 1.DISPLAY TYPE: STN/YELLOW GREEN MODE
 - 2.VIEWING DIRECTION: 6:00
 - 3.POLARIZER MODE: TRANSMISSIVE/POSITIVE
 - 4.DRIVE METHOD: 1/16 DUTY 1/5 BIAS
 - 5.LCD OPERATING VOLTAGE: 4.6V
 - 6.OPERATING TEMP: 0°C~+50°C
 - 7.STORAGE TEMP: -20°C~+60°C
 - 8.CONTROLLER: S6A0069X01-C0CX(KS0066UP-00CC)
 - 9.BACKLIGHT: LED
 - 10.BEZEL IS TO BE PAINTED BLACK
 - 11.UNMARKED TOLERANCES: ±0.3mm

 TIAN-MA MICROELECTRONICS CO. 6/F., CASTIC Building, Shennan Road, Central, Shenzhen, China		
DRAWN BY:	TITLE: TM204KBF6	
CHECKED BY:	DWG NO: G-1	SCALE
APPROVED BY:	DWG NAME: TM204KBF6G-1	UNIT: mm
CONFIRMED BY:	SHEET NO: OF	