

SPECIFICATIONS

Mechanical

Contact Retention Force: 1.36kg min.

Electrical

Voltage Rating: 250V

Current Rating: 3.0A

Contact Resistance: 20mW max.

Dielectric Withstanding Voltage: 600V AC

Insulation Resistance: 1000MW

Physical

Housing: Thermoplastic, UL 94V-0 rated in Nature Color

Contact: Copper alloy

Plating: See "ORDERING INFORMATION"


Operating Temperature: -40 to +105

Wire-to-Board Header


HF01 Series

Vertical, T/H Type

2.54mm [.100"] Pitch



DRAWING



ORDERING INFORMATION

PRODUCT NO.: HF01**0

Header _____
 Friction Lock _____
 Termination & Contact Type _____
 Contact Area Plating
 0= Tin/Lead
 No. of Pos.
 02 = 2 Positions
 03 = 3 Positions
 04 = 4 Positions
 05 = 5 Positions

P/N	DIM. A	DIM. B	DIM. C
HF01050	15.29 [.602]	13.21 [.520]	10.16 [.400]
HF01040	12.75 [.502]	10.67 [.420]	7.62 [.300]
HF01030	10.21 [.402]	8.13 [.320]	5.08 [.200]
HF01020	7.40 [.291]	5.33 [.210]	2.54 [.100]