


DETAIL A:



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
VSS	VDD	VO	U/T	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	CS1	CS2	RST	VEE	A	K

- NOTES:
1. DISPLAY TYPE: STN/YELLOW MODE
  2. VIEWING DIRECTION: 6:00
  3. POLARIZER MODE: TRANSFLECTIVE/POSITIVE
  4. DRIVE METHOD: 1/64 DUTY 1/9 BIAS
  5. LCD OPERATING VOLTAGE: 11.0V
  6. OPERATING TEMP: -20°C~+70°C
  7. STORAGE TEMP: -30°C~+80°C
  8. CONTROLLER: S6B0108A01-COCX
  9. BACKLIGHT: LED<2.1V>
  10. BUILT IN DC-DC
  11. BEZEL IS TO BE PAINTED BLACK
  12. ALL UNMARKED TOLERANCES: ±0.3mm

**TIAN-MA MICROELECTRONICS CO.**  
 22/F., HANGJIU Building, Shennan Road, Central, Shenzhen, China

DRAWN BY:	TITLE: TM12864LBCW8	
CHECKED BY:	DWG NO: G-1	
APPROVED BY:	DWG NAME: TM12864LBCW8-1	
CONFIRMED BY:	SHEET NO: DP	