

TRV4

- 40A continuous rating 85°C
- 1A&1C arrangements
- Plug-in or PC board terminals
- Optional mounting bracket
- Conform to RoHS,ELV directive



28×28×25
28×31.8×41

ORDERING CODE 订购代码

TRV4	L	—12V (D1)	—	Z	—	F	—	P
1	2	3	4	5	6	7		
1. Relay Model 继电器型号				5. 触点转换形式				
2. Coil Power 线圈功率 D=1.9W; L=1.6W				Z: Form C				
3. Coil Nominal Voltage 线圈额定电压 6,12,24VDC				H: Form A				
4. Nil: Standard (标准)				D: Form B				
R1: Coil parallel with 1/2W resistor 680 Ω for Coil voltage 12VDC; 2700 Ω for coil voltage 24VDC				6. F: WITH BRACKET(有背)				
D1/D2: With diode(详见安装图)				Nil: WITHOUT BRACKET(无背)				
				7. P: PCB Type				
				Nil: B Type				

COIL DATA 线圈参数 (at 20°C)

Nominal Voltage额定电压(VDC)	6	12	24	1.6W
Coil Resistance线圈阻值(Ω ±10%)	23	90	360	
Rated Current额定电流(mA)	267	133	67	
Max Operate Voltage 最大吸合电压(VDC)	3.9	7.8	15.6	
Min Release Voltage最小释放电压(VDC)	0.6	1.2	2.4	1.9W
Coil Resistance线圈阻值(Ω ±10%)	19	76	300	
Rated Current额定电流(mA)	317	158	79	
Max Operate Voltage 最大吸合电压(VDC)	3.9	7.8	15.6	
Min Release Voltage最小释放电压(VDC)	0.6	1.2	2.4	
Max Applicable Voltage 最大过载电压	70°C时额定电压的130%，23°C时额定电压的170%			

CONTACT DATA 触点参数

Contact Form触点形式	1H/1Z
Contact Material触点材料	Silver Alloy
Load负载	Resistive load(COS Φ 1)
Contact Ratings触点负载	NO: 40A 14VDC NC: 30A 14VDC
Max Switching Voltage最大转换电压	30VDC
Max Switching Current最大转换电流	40A
Max Switching Power 最大转换功率	560W
Contact Resistance接触电阻	100mΩ Max at 6VDC 1A
Life Expectancy寿命	Electrical 电气寿命: 100,000 Operations(at30Operations/minute)
	Mechanical机械寿命: 10,000,000 Operations(at300Operations/minute)

■ CHARACTERISTICS DATA 性能参数

Insulation Resistance 绝缘阻值	100M Ω Min at 500VDC
Dielectric Strength Between Open Contacts 触点间耐压	500VAC(for one minute)
Between Contacts and coil 触点与线圈间耐压	750VAC(for one minute)
Operate Time 吸合时间	10ms
Release Time 释放时间	10ms
Temperature Range 环境温度	-40 $^{\circ}$ C to +85 $^{\circ}$ C
Shock Resistance 冲击	Operating Extremes 动作极限: 10G
	Damage Limits 破坏极限: 20G
Vibration Resistance 振动	10-40Hz, 1.5mm
Max. switching frequency 最大转换频率	Mechanical: 18,000operations/hr
	Electrical: 1,800operations/hr
Humidity 湿度	40-85%
Weight 重量	Approx 40g

■ ENGINEERING DATA 设计参数



