



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 4. RATING: 50mA @ 12VDC
 5. OPERATING FORCE: 320 ± 80gf
 6. TRAVEL: 0.35mm ±0.1mm
 7. CONTACT RESISTANCE: 100 MILLI OHMS MAX. (INITIAL)
 8. MECHANICAL/ELECTRICAL LIFE 100,000 CYCLES MIN.
 9. INSULATION RESISTANCE: 100M OHMS MIN. AT 500VAC
 11. DIELECTRIC STRENGTH: 250VAC FOR 1 MINUTE
 10. PACKAGING: 700 PCS. PER TAPE & REEL
 11. 2002/95/EC (ROHS) COMPLIANT
 - 12.▲ DENOTES CRITICAL PARAMETER



TITLE TL3300DF320Q

A	19636	Released For Production	2/1/11	BGL
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

SCALE 2:1 DATE 1/31/2011

DR BGL DWG N301107

REV A