






P.C.B. MOUNTING



CIRCUIT: SPST



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. TERMINAL NUMBERS FOR REF. ONLY
3. TOLERANCE: $X.X \pm 0.4$
 $X.XX \pm 0.25$
- ▲ 4. CONTACT MATERIAL: SILVER
5. RATING: 12VDC @ 50mA
6. TRAVEL: $0.25 \pm 0.2/-0.1$ mm
- ▲ 7. OPERATING FORCE: 65 ± 20 gf
8. ELECTRICAL LIFE: 5 MILLION CYCLES
9. CONTACT RESISTANCE: 50mΩ MAX.
10. ▲ DENOTES CRITICAL PARAMETER
11. 2002/95/EC (ROHS) COMPLIANT
- ▲ 12. PACKAGING: 750 PIECES/PER POLY BAG

B	20957	CORRECT OPERATING FORCE	1/8/13	EBP
A	17554	RELEASED FOR PRODUCTION	8/21/07	BF
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY
TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED



TITLE LL1105AF065Q

SCALE 4:1

DATE 8/21/2007

DR	
BF	

DWG P010247

REV
B