LFV230-XXSGBCPV0300 LFV200



LEVEL SENSORS

LFV230-XXSGBCPV0300 | LFV200

LEVEL SENSORS



Ordering information

Туре	Part no.
LFV230-XXSGBCPV0300	6044007

Other models and accessories -> www.sick.com/LFV200



Detailed technical data

Features

Medium	Fluids
Measurement	Switch
Probe length	300 mm
Process pressure	-1 bar 64 bar
Process temperature	-40 °C +100 °C
Fill material density	$\geq 0.7 \text{ g/cm}^3$
Porformanco	

Performance

Accuracy of sensor element	± 2 mm
Repeatability	≤ 1 mm
Viscosity	0.1 mPas 10,000 mPas
Resolution	≤ 1 mm
Response time	500 ms

Electronics

Supply voltage	20 V AC/DC 253 V AC/DC
Power consumption	< 10 mA
Initialization time	<3s
VDE protection class 2	✓
Electrical connection	Valve plug DIN 43650
Hysteresis	2 mm
Output current	< 250 mA
Inductive load	≤1H
Capacitive load	100 nF
Enclosure rating	IP 65
Temperature drift	0.03 mm/K
Mechanics	

Wetted parts

LFV230-XXSGBCPV0300 | LFV200

LEVEL SENSORS

Process connection	G ¾ A PN 64
Housing material	Stainless steel 1.4404, PEI

Ambient data

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

