



Thin-film Diplexer

For 2400-2500MHz / 4900-5950MHz

TFSD10055950-5001C1A

1.0x0.5mm [EIA 0402]*

* Dimensions Code JIS[EIA]


Thin-film Diplexer

Conformity to RoHS Directive


For 2400-2500MHz / 4900-5950MHz

TFSD10055950-5001C1A

SHAPES AND DIMENSIONS



RECOMMENDED LAND PATTERN



The recommended distance to the PCB ground plane is 0.2mm.

Line width should be designed to match 50Ω characteristic impedance, depending on PCB material and thickness.

○ RoHS Directive Compliant Product: See the following for more details related to RoHS Directive compliant products. <http://product.tdk.com/en/environment/rohs/>

- All specifications are subject to change without notice.
- Before using these products, be sure to request the delivery specifications.

TFSD10055950-5001C1A

ELECTRICAL CHARACTERISTICS

LOW-BAND

Item	Frequency Range (MHz)	Min.	Typ.	Max.
Insertion Loss (dB)	2400 to 2500	—	0.43	0.50
Return Loss (dB)	2400 to 2500	10	21.4	—
Attenuation (dB)	4800 to 5000	20	23.1	—
	7200 to 7500	20	29.2	—
Characteristic Impedance (Ω)				50 (Nominal)

· Ta: +25±5°C

HIGH-BAND

Item	Frequency Range (MHz)	Min.	Typ.	Max.
Insertion Loss (dB)	4900 to 5950	—	0.49	0.65
Return Loss (dB)	4900 to 5950	10	22.5	—
Attenuation (dB)	824 to 915	20	25.6	—
	1800 to 2500	20	24.1	—
	9800 to 11900	18	21.0	—
Characteristic Impedance (Ω)				50 (Nominal)

· Ta: +25±5°C

COMMON

Item	Frequency Range (MHz)	Min.	Typ.	Max.
Isolation (dB)	DC to 2500	20	23.4	—
	4900 to 5950	20	23.9	—
Return Loss (dB)	2400 to 2500	10	19.5	—
	4900 to 5950	10	20.4	—
Characteristic Impedance (Ω)				50 (Nominal)

· Ta: +25±5°C

TEMPERATURE RANGE

Operating temperature (°C)	Storage temperature (°C)
-40 to +85	-40 to +85

MSL

Moisture Sensitivity Level (MSL)
1


- All specifications are subject to change without notice.
- Before using these products, be sure to request the delivery specifications.

TFSD10055950-5001C1A


FREQUENCY CHARACTERISTICS

LOW-BAND


Insertion Loss



Return Loss




Attenuation




HIGH-BAND


Insertion Loss



Return Loss



Attenuation




- All specifications are subject to change without notice.
- Before using these products, be sure to request the delivery specifications.

TFSD10055950-5001C1A


FREQUENCY CHARACTERISTICS

COMMON

Return Loss




Isolation



- All specifications are subject to change without notice.
- Before using these products, be sure to request the delivery specifications.

TFSD10055950-5001C1A

RECOMMENDED REFLOW PROFILE



Soaking			Working				Soldering		Peak
Temp.	Temp.	Time	Temp.	Temp.	Temp.	Time	Temp.	Time	Temp.
T1	T2	t1	T3	T4	T4	t3	T5	t4	T6
150°C	180°C	60 to 120s	217°C	230°C	230°C	more than 45s	247 to 253°C	within 10s	260°C max.

- All specifications are subject to change without notice.
- Before using these products, be sure to request the delivery specifications.

REMINDERS FOR USING THESE PRODUCTS

Before using these products, be sure to request the delivery specifications.

SAFETY REMINDERS

Please pay sufficient attention to the warnings for safe designing when using these products.

REMINDERS

The products listed on this catalog are intended for use in general electronic equipment (AV equipment, telecommunications equipment, home appliances, amusement equipment, computer equipment, personal equipment, office equipment, measurement equipment, industrial robots) under a normal operation and use condition.

The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property.

Please understand that we are not responsible for any damage or liability caused by use of the products in any of the applications below or for any other use exceeding the range or conditions set forth in this catalog.

- | | |
|---|--|
| (1) Aerospace/Aviation equipment | (8) Public information-processing equipment |
| (2) Transportation equipment (cars, electric trains, ships, etc.) | (9) Military equipment |
| (3) Medical equipment | (10) Electric heating apparatus, burning equipment |
| (4) Power-generation control equipment | (11) Disaster prevention/crime prevention equipment |
| (5) Atomic energy-related equipment | (12) Safety equipment |
| (6) Seabed equipment | (13) Other applications that are not considered general-purpose applications |
| (7) Transportation control equipment | |

When using this product in general-purpose applications, you are kindly requested to take into consideration securing protection circuit/equipment or providing backup circuits, etc., to ensure higher safety.