

1 2 3 4 5 6 7

Signature	Revision History	Date	Rev.
LIBRA	For Bulk Production	June30,2011	01

RoHS Compliant

USB 3.0 A TYPE MALE

MICRO USB 3.0 B TYPE MALE

NOTES:

1.CABLE: UL 2725 [28AWG(7/0.127TC)*1P+D28AWG(7/0.127TC)+AL/MY]*2C+28AWG(7/0.127TC)*1P+28AWG(7/0.127TC)*2C +D28AWG(7/0.127TC)+AL/MY+B(85% COVERAGE ALM) OD=5.5±0.20mm JACKET COLOR: BLACK
CABLE MUST PRINT: E***** AWM STYLE 2725 80°C 30V VW-1

2.CONNECTOR:

P1 : USB 3.0 A/M, SOLDER, BLUE INSULATION, 3u GOLD PLATED CONTACTS, NICKEL PLATED SHELL
P2 : MICRO USB 3.0 B/M, SOLDER, BLACK INSULATION, 3u GOLD PLATED CONTACTS, NICKEL PLATED SHELL

3.HOOD: MOLDED TYPE,PVC 45P,COLOR:BLACK.

4.ELECTRICLE TEST:

(1)100% OPEN SHORT & MIS WIRE TEST.
(2)CONTACT RESISTANCE 3 ohm Max .
(3)INSULATION RESISTANCE 10M ohm Min .
(4)HI-POT TEST:DC 300V/10ms

PIN ASSIGNMENT			
P1		P2	
1	RED	1	VCC
2	WHITE	2	-DATA
3	GREEN	3	+DATA
4	BLACK	5	GND_PWRt
5	BLUE	6	SDP1-
6	YELLOW	7	SDP1+
7	D.W	8	SDP1,SDP2_Drain
8	PURPLE	9	SDP2-
9	ORANGE	10	SDP2+
SHELL	B.D	SHELL	

Cross Section:

Date		Name	Part No. AK-300116-050-S EAN:4016032283317		
Drawn by	June30,2011	Libra			
Checked by					
Approved by			Title USB 3.0 A/M - MICRO USB 3.0 B/M CABLE		
ASSMANN Electronic GmbH			Scale	N/A	Sheet 1/2
			Unit	MM	

1 2 3 4 5 6 7