

USB over Cat5 Extender Kit

MODEL NUMBER: U007-40M





Description

Tripp Lite's USB 1.1 over Cat5 Extender Kit allows you to connect your computer to a USB 1.1 peripheral up to 150 feet away using ordinary Cat5/Cat5e/Cat6 cable. The transmitter and receiver kit is bus-powered, so no

external power supply is required. Plug-and-play; no software or drivers needed. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Features

- Locate a USB 1.1 peripheral up to 150 feet from your computer
- Bus Powered no additional AC adapters required
- Uses readily available Cat5/Cat5e/Cat6 cable (not included)
- Transfer rates of 1.5Mbps to 12Mbps
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW		
Cable Type	USB	
INPUT		
Cable Length (ft.)	131	
Cable Length (m)	39.93	
PHYSICAL		
Color	Black	
Transmitter Unit Height (in.)	0.9	

Highlights

- Locate a USB 1.1 peripheral up to 150 feet from your computer
- Uses readily available Cat5/Cat6
 cable
- Bus-powered; no external power supply required
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Applications

• Use with USB 1.1 peripherals that need to exceed the 16 ft. (5 m.) distance limitation

Package Includes

- Local transmitter unit
- Remote receiver unit
- Owner's manual



Transmitter Unit Width (in.)	1.8	
Transmitter Unit Depth (in.)	2.6	
Receiver Unit Height (in.)	0.9	
Receiver Unit Width (in.)	1.8	
Receiver Unit Depth (in.)	2.6	
CONNECTIONS		
Connector A	USB A (MALE)	
Connector B	RJ45 (FEMALE) (X2)	
Connector C	USB A (FEMALE)	
SPECIAL FEATURES		
Chromebook Compatible	Yes	
CERTIFICATIONS		
CERTIFICATIONS		
Approvals	CE, FCC, RoHS Compliant	
WARRANTY		
Product Warranty Period (Worldwide)	1-year limited warranty	
	1-year limited warranty	

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.