

## Features

- Surface Mount
- 1:1 Impedance Ratio
- CT on Secondary
- RoHS\* Compliant version of the ETC1-1T
- Tape and reel packaging available

## Image



## Description

M/A-COM's MABAES0060 is a RoHS compliant device that is equivalent to the ETC1-1T transformer. This device is a 1:1 RF flux coupled transformer in a low cost, surface mount package. Ideally suited for high volume cellular and wireless applications. Typical applications include single to balanced mode conversion and impedance matching. The MABAES0060 transformer is offered in an SM-22 surface mount package and is designed to be utilized in both standard reflow and high temperature soldering reflow profiles.

## Ordering Information

Part Number	Package
MABAES0060	Tape and Reel (2000 piece reels)


## Electrical Specifications: $T_A = 25^\circ\text{C}$ , $Z_0 = 50\Omega$ <sup>1</sup>

Parameter	Test Conditions	Frequency	Units	Min	Typ	Max
RF Frequency	—	0.3 - 200	MHz	—	—	—
Insertion Loss	—	0.3 - 200	dB	—	—	1.5
Amplitude Imbalance	—	0.3 - 50	dB	—	—	0.1
		0.3 - 200	dB	—	—	0.5
Phase Imbalance	—	0.3 - 50	Degrees	—	—	1.0
		0.3 - 200	Degrees	—	—	5.0
Input Return Loss	—	0.3 - 200	dB	—	—	10.0
		5 - 120	dB	—	—	15.0

## Pin Configuration

Pin No.	Function
1	Secondary
2	Secondary CT
3	Secondary Dot
4	Primary Dot
5	Primary

## Schematic



# MABAES0060



E-Series RF 1:1 Flux Coupled Transformer  
0.3 – 200 MHz


M/A-COM Products  
Advanced - Rev. V4

## Absolute Maximum Ratings <sup>1,2</sup>

Parameter	Absolute Maximum
RF Power	250 mW
DC Current	240 mA <sup>2</sup>
Operating Temperature	-40°C to +85°C
Storage Temperature	-55°C to +125°C


1. Operation of this device above any one of these parameters may cause permanent damage.
2. The maximum DC current applies to the secondary center tap in applications where the secondary is balanced.

## Outline Drawing — SM-22




## Typical Performance Curves Over Bandwidth (300kHz - 200MHz)


**Insertion Loss**




**Phase Unbalance**



**Amplitude Unbalance**



**Input Return Loss**



2

**ADVANCED:** Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.  
**PRELIMINARY:** Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples and/or test data may be available. Commitment to produce in volume is not guaranteed.

• **North America** Tel: 800.366.2266 • **Europe** Tel: +353.21.244.6400  
• **India** Tel: +91.80.4155721 • **China** Tel: +86.21.2407.1588  
Visit [www.macomtech.com](http://www.macomtech.com) for additional data sheets and product information.

M/A-COM Technology Solutions Inc. and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice.