



All dimensions are in mm; tolerances:  $\pm 3$  mm for  $A \leq 300$  mm;  $\pm 1\%$  for  $A > 300$  mm  
\*differing for  $A \leq 150$  mm

**Available variants**

Type	max. Insertion loss at 20 GHz	Marking	Weight (g) / pce
L99-813-XXF	$\leq 0.0050$ dB/mm * A mm + 0.60 dB	ROSENBERGER YYY- L99-813-XXF FAC-RRRRRRR ssss	$0.011$ g/mm * A mm + 10.7 g

XX – length in cm      F = 2 Channel      A = XX\*10  
WW – week              YYYY – year              ssss – serial no.      FAC – Factory Code      RRRRRR – lot nr.

Note: max. Insertion Loss:  
First constant = Cable attenuation in dB /mm; Second Constant = Connector left and Connector right +needed Adaptor  
  
Weight:  
First constant = Cable- and Armour- weight per mm; Second Constant = Connector left and Connector right weight per pce

**Assembly parts**

Connector left	Mini Coax plug	23S103-270L3
Connector left	Mini Coax jack	23K103-270L3
Connector right	SMA plug	32S102-270L5
Cable	cable	RTK 047
Housing	23Z121-008	(2 channel) Luranyl KR 2402 gray

# Technical Data Sheet

# Rosenberger

Cable assembly  
Mini coax plug/jack – SMA PLUG

## L99-813-XXF

### Electrical data

Impedance	50 $\Omega$
Frequency	DC to 20 GHz
Return loss <sup>1</sup>	$\geq 16$ dB, DC to 20 GHz
Insertion loss <sup>1</sup>	see table available variants
Phasematched by pairs	max. 2ps delay difference

#### Individual testing:

The S-Parameters (S11; S22; S21; S12) will be tested and the cable pairs are measured for phase matching

<sup>1</sup> Return Loss and Insertion Loss includes the measurement adaptor

### Mechanical data

Minimum bend radius:	
Single	5.1 mm
Multiple	10.2 mm

### Environmental data

Temperature range	-40°C to +115°C
RoHS	compliant

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Martin Moder	06.04.16	M. Scherbauer	13.04.16	a00	16-s130	K. Mitterer	13.04.16

  

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.de">www.rosenberger.de</a>	Tel. : +49 8684 18-0 Email : <a href="mailto:info@rosenberger.de">info@rosenberger.de</a>	Page 2 / 2
--	--	---------------