

MLZ2012N4R7LT000









Applications	Commercial Grade
Feature	Shield Magnetic Shield Multilayer Multilayer Ferrite Core
Series Type	MLZ
Status	Production
Brand	TDK



	Size	
Length(L)	2.00mm ±0.20mm	
Width(W)	1.25mm ±0.20mm	
Thickness(T)	0.85mm ±0.20mm	
Recommended Land Pattern (A)	0.80mm Nom.	
Recommended Land Pattern (B)	1.00mm Nom.	
Recommended Land Pattern (C)	1.20mm Nom.	

Electrical Characteristics			
Inductance	4.7μH ±20% at 2MHz		
Rated Current (L Change) [Typ.]			
Rated Current (L Change) [Max.]	130mA (50% Down)		
Rated Current (Temperature Rise) [Typ.]	600mA (20°C Rise)		
Rated Current (Temperature Rise) [Max.]	130mA (20°C Rise)		
DC Resistance [Typ.]	180mΩ		
DC Resistance [Max.]	234mΩ		
Self Resonant Frequency [Min.]			
Self Resonant Frequency [Typ.]			
Q [Min.]			
Q [Typ.]			

Other			
Operating Temp. Range (Including Self-Temp. Rise)	-55 to 125°C		
	Wave (Flow)		
Soldering Method	Reflow		
	Iron Soldering		
AEC-Q200	No		
Packing	Punched (Paper)Taping [180mm Reel]		
Package Quantity	4000pcs		
Whates are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.	0.01g		

MLZ2012N4R7LT000














Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)











[!] Images are for reference only and show exemplary products.

[!] This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.

MLZ2012N4R7LT000










Associated Images



[!] Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.