




SR1020C THRU SR10A0C

SCHOTTKY BARRIER RECTIFIER

Reverse Voltage - 20 to 100 Volts Forward Current - 10.0 Amperes

TO-220AB



Dimensions in inches and (millimeters)

FEATURES

- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- Construction utilizes void-free molded plastic technique
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed: 250°C, 0.25" (6.35mm) from case for 10 seconds

MECHANICAL DATA

Case: TO-220AB molded plastic body

Terminals: Leads solderable per MIL-STD-750, Method 2026

Polarity: As marked

Mounting Position: Any

Weight: 0.080 ounce, 2.24 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

	SYMBOLS	SR 1020C	SR 1030C	SR 1040C	SR 1045C	SR 1050C	SR 1060C	SR 1070C	SR 1080C	SR 1090C	SR 10A0C	UNITS
Maximum repetitive peak reverse voltage	V _{RRM}	20	30	40	45	50	60	70	80	90	100	VOLTS
Maximum RMS voltage	V _{RMS}	14	21	28	32	35	42	49	56	63	70	VOLTS
Maximum DC blocking voltage	V _{DC}	20	30	40	45	50	60	70	80	90	100	VOLTS
Maximum average forward rectified current (see fig.1)	I _(AV)											Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}											Amps
Maximum instantaneous forward voltage at 5.0A	V _F				0.65		0.75		0.85			Volts
Maximum DC reverse current TA=25°C at rated DC blocking voltage TA=100°C	I _R							1.0				mA
					15.0			50.0				
Typical junction capacitance (NOTE 1)	C _J				550			450				pF
Typical thermal resistance (NOTE 2)	R _{qjc}						2.0					°C/W
Operating junction temperature range	T _J			-65 to +125				-65 to +150				°C
Storage temperature range	T _{STG}						-65 to +150					°C

Note: 1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.

2. Thermal resistance from junction to case

RATINGS AND CHARACTERISTIC CURVES SR1020C THRU SR10A0C

AVERAGE FORWARD RECTIFIED CURRENT,
AMPERES





FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT



INSTANTANEOUS FORWARD
CURRENT, AMPERES






FIG. 4-TYPICAL REVERSE CHARACTERISTICS



JUNCTION CAPACITANCE, pF



TRANSIENT THERMAL IMPEDANCE,
C_W

