



All dimensions are in mm; tolerances according to ISO 2768 c-H

Type	Length "a" (mm)
LH1-032-120-B	120 ±3
LH1-032-67-B	67 ±3

**Documents**

Technical data sheet Fakra connector      59S50E-1H1A4-Y  
 Technical data sheet Micro RF connector      15S201-1H1L5  
 Technical data sheet Cable      RTK 013aaz

**Electrical data**

Impedance	50 Ω
Frequency	DC to 3 GHz
Return loss	≥ 15 dB, DC to 3 GHz (*)
Insertion loss	≤ 1 dB to 3 GHz (*)

(\* Limitations are possible; exact values have to be measured.

**Mechanical data**

Minimum bend radius	repeated 8xØ, single 4xØ
---------------------	--------------------------

**Environmental data**

Temperature range	-40°C to +90°
-------------------	---------------

**Packing**

Standard	50 pcs. in plastic bag
----------	------------------------

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Manfred Ruf	13/01/09	Thomas Höfling	11/03/10	100	09-v309	Manfred Ruf	11/03/10
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.de">www.rosenberger.de</a>					Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: <a href="mailto:info@rosenberger.de">info@rosenberger.de</a>		Page 2 / 2