PASTERNACK®
THE ENGINEER'S RF SOURCE

WR-90 Flexible Waveguide Twist With a UG-39/ Flange Operating From 8.2 GHz to 12.4 GHz

Waveguide Twists Technical Data Sheet PE-W90TF005-12

Features

- Twelve inch long WR-90 waveguide
- Twistable
- Flexes in both the E and H plane
- Neoprene sleeve allows pressurization
- 8.2 GHz to 12.4 GHz Frequency Range
- Brass flanges with a silver p

Applications

- Simplifes positioning reflectors for line of sight microwave radio links.
- Test Benches
- Eliminates installation problems caused by misalignment.
- Allows expansion/contraction due to thermal issues.
- Pressurized waveguide systems
- Provides vibration isolation
- Microwave Radio

Description

The PE-W90TF005-12 is part of Pasternack's family of flexib range. The waveguide body is made of a helically wound sil E and H planes without impairing VSWR or attenuation. The waveguide is covered by a neoprene jacket which protects the waveguide, provides mechanical support and allows the wave

Electrical Specifcations

Description	Minimum	Typical	Maximum	Units
Frequency Range	8.2		12.4	GHz
VSWR		1.1:1		
Insertion Loss		0.15		dB

Mechanical Specifcations

Waveguide Size	WR-90
Waveguide Design	Twistable
Section Length	12 in [304.8 mm]
E-Plane Minimum Bend Radius, One Time	5 in [63.5 mm]
E-Plane Minimum Bend Radius, Repeated	10 in [254 mm]
H-Plane Minimum Bend Radius, One Time	5 in [127 mm]
H-Plane Minimum Bend Radius, Repeated	20 in [508 mm]
Maximum Offset Rotation, One Time	90 degrees/ft
Maximum Offset Rotation, Repeated	24 degrees/ft
Maximum Operating Pressure	45 psig

Click the following link (or enter part number in "SEARC price, inventory WR-90 Flexible Waveguide Twist With a UG-12.4 GHz PE-W90TF005-12

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623
Phone: (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451
Sales@Pasternack.com • Techsupport@Pasternack.com

ISO 9001 : 2008 Registered

© 2015 Pasternack Enterprises All Rights Reserved

PASTERNACK
THE ENGINEER'S RF SOURCE

WR-90 Flexible Waveguide Twist With a UG-39/U Flange Operating From 8.2 GHz to 12.4 GHz

Waveguide Twists Technical Data Sheet PE-W90TF005-12



WR-90 Flexible Waveguide Twist With a UG-39/U Flange Opera
has same day shipment for domestic and worldwide and most orders
99% availability and are part of the broadest selection in

Click the following link (or enter part number in "SEARCH"
inventory and get more information on the WR-90 Flexible Waveguide Twist With a UG-39/U
PE-W90TF005-12

URL: http://www.pasternack.com/wr-90-flexible-waveguide-twis

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623
Phone: (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451
Sales@Pasternack.com • Techsupport@Pasternack.com

ISO 9001 : 2008 Registered

© 2015 Pasternack Enterprises All Rights Reserved