



CX16 TELEMETRY CRYSTAL

24 MHz to 50 MHz

Low Profile, Ultra-Miniature
Surface Mount Quartz Crystal

DESCRIPTION

When miniaturization is paramount, Statek's low profile CX16 AT quartz crystal is an excellent choice. This crystal has a typical footprint of 2.0 mm x 1.2 mm, and a typical height of 0.43 mm. The resonator is manufactured using Statek's photolithographic and chemical milling processes and then sealed within a ceramic package for high stability and low aging. Available with tight calibration tolerances and high stability over temperature and fast start-up times, this crystal is well suited for applications that have a space restraint and require a crystal with a low profile.

FEATURES

- Ultra-miniature, surface mount design
- Ultra-low profile
- Hermetically sealed ceramic package
- High shock and vibration survival
- Excellent aging characteristics
- Full military testing available
- Designed and manufactured in the USA

APPLICATIONS


Medical

- Medical Telemetry
- Pacemakers
- Defibrillators
- Neurostimulators
- Infusion Pumps
- Cochlear Implants



ceramic lid

PACKAGE DIMENSIONS




TYPICAL

DIM	inches	mm
A	0.079	2.00
B	0.047	1.20
C	-	-
D	0.025	0.64

THICKNESS (DIM C)

Lid	Termination	Typical	
		inches	mm
Ceramic	SM1	0.017	0.43
	SM2/SM4	0.018	0.44
	SM3/SM5	0.019	0.47

LAND PATTERN



10200 Rev B



SPECIFICATIONS

Specifications are typical at 25°C unless otherwise noted. Specifications are subject to change without notice.

Fundamental Frequency	<u>24 MHz</u>	<u>26.5 MHz</u>
Motional Resistance $R_1(\Omega)$	100	90
Motional Capacitance C_1 (fF)	1.3	1.4
Quality Factor Q (k)	30	30
Shunt Capacitance C_0 (pF)	0.6	0.6
Calibration Tolerance	±100 ppm, or tighter as required	
Load Capacitance	10 pF (unless specified otherwise)	
Drive Level	100 μW MAX	
Frequency-Temperature Stability ¹	±50 ppm to ±10 ppm (Commercial)	
	±100 ppm to ±20 ppm (Industrial)	
	±100 ppm to ±30 ppm (Military)	
Aging, first year	3 ppm MAX (better than 1 ppm available)	
Shock, survival	5,000 g, 0.3 ms, 1/2 sine	
Vibration, survival ²	20 g, 10-2,000 Hz swept sine	
Operating Temp. Range	-10°C to +70°C (Commercial)	
	-40°C to +85°C (Industrial)	
	-55°C to +125°C (Military)	
Storage Temp. Range	-55°C to +125°C	
Max Process Temperature	260°C for 20 sec.	


1. Does not include calibration tolerance. The characteristics of the frequency stability over temperature follow that of the AT thickness-shear mode.
 2. Per MIL-STD-202G, Method 204D, Condition D. Random vibration testing also available.

TERMINATIONS

Designation	Termination
SM1	Gold Plated (Lead Free)
SM2	Solder Plated
SM3	Solder Dipped
SM4	Solder Plated (Lead Free)
SM5	Solder Dipped (Lead Free)

Max Process Temperature 260°C for 20 sec.

EQUIVALENT CIRCUIT



R_1 Motional Resistance L_1 Motional Inductance
 C_1 Motional Capacitance C_0 Shunt Capacitance

PACKAGING OPTIONS

- Tray Pack
- 8mm tape, 7" or 13" reels (Per EIA 481)

HOW TO ORDER CX16 AT CRYSTALS

CX16	S	C	SM4	—	24.0M	,	30	/	10	/	—	/	I	,	3 pF
Blank = Standard S = Special or custom	C = Ceramic Lid	SM1 = Gold Plated (Lead Free) SM2 = Solder Plated SM3 = Solder Dipped SM4 = Solder Plated (Lead Free) SM5 = Solder Dipped (Lead Free)	Frequency M = MHz	Calibration Tolerance @ 25°C (in ppm)	Frequency Stability over Temp. Range (in ppm)	Temp. Range: C = -10°C to +70°C I = -40°C to +85°C M = -55°C to +125°C S = Customer Specified	Load Capacitance (Customer Specified)								