

MBRF3035CT - MBRF30150CT

Isolated 30.0 AMPS. Schottky Barrier Rectifiers

ITO-220AB




Features

- ✧ Plastic material used carries Underwriters Laboratory Classifications 94V-0
- ✧ Metal silicon junction, majority carrier conduction
- ✧ Low power loss, high efficiency
- ✧ High current capability, low forward voltage drop
- ✧ High surge capability
- ✧ For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications
- ✧ Guardring for overvoltage protection
- ✧ High temperature soldering guaranteed:
260°C/10 seconds, 0.25" (6.35mm) from case

Mechanical Data

- ✧ Cases: ITO-220AB molded plastic body
- ✧ Terminals: Pure tin plated, lead free. solderable per MIL-STD-750, Method 2026
- ✧ Polarity: As marked
- ✧ Mounting position: Any
- ✧ Mounting torque: 5 in-lbs. Max.
- ✧ Weight: 0.08 ounce, 2.24 grams



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%

| Type Number | Symbol | MBRF 3035 CT | MBRF 3045 CT | MBRF 3050 CT | MBRF 3060 CT | MBRF 3090 CT | MBRF 30100 CT | MBRF 30150 CT | Units | |
|---|-----------------|------------------------------|--------------|--------------|--------------|------------------------------|------------------------------|---------------|----------|---------------------------|
| Maximum Recurrent Peak Reverse Voltage | V_{RRM} | 35 | 45 | 50 | 60 | 90 | 100 | 150 | V | |
| Maximum Working Peak Reverse Voltage | V_{RMS} | 24 | 31 | 35 | 42 | 63 | 70 | 105 | V | |
| Maximum DC Blocking Voltage | V_{DC} | 35 | 45 | 50 | 60 | 90 | 100 | 150 | V | |
| Maximum Average Forward Rectified Current at $T_c=130^\circ\text{C}$ Total device Per Leg | $I_{(AV)}$ | 30 15 | | | | | | | | A |
| Peak Repetitive Forward Current Per leg (Rated V_R , Square Wave, 20KHz) at $T_c=130^\circ\text{C}$ | I_{FRM} | 30 | | | | | | | | A |
| Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method) | I_{FSM} | 200 | | | | | | | | A |
| Peak Repetitive Reverse Surge Current (Note 1) | I_{RRM} | 1.0 | | | 0.5 | | | | | A |
| Maximum Instantaneous Forward Voltage at (Note 2) $I_F=15\text{A}, T_c=25^\circ\text{C}$ $I_F=15\text{A}, T_c=125^\circ\text{C}$ $I_F=30\text{A}, T_c=25^\circ\text{C}$ $I_F=30\text{A}, T_c=125^\circ\text{C}$ | V_F | 0.70 0.60 0.82 0.73 | | 0.75 0.65 | | 0.84 0.70 0.94 0.82 | 0.95 0.80 1.05 0.92 | | V | |
| Maximum Instantaneous Reverse Current @ $T_c=25^\circ\text{C}$ at Rated DC Blocking Voltage Per Leg @ $T_c=125^\circ\text{C}$ (Note 2) | I_R | 0.2 20 | | 0.2 15 | | 0.2 10 | | | mA mA | |
| Voltage Rate of Change, (Rated V_R) | dV/dt | 1,000 | | | | | | | | V/ μs |
| Typical Junction Capacitance | C_j | 580 | | 480 | | 360 | | | | pF |
| Maximum Thermal Resistance Per Leg (Note 3) | $R_{\theta JC}$ | 1.0 | | | 1.5 | | | | | $^\circ\text{C}/\text{W}$ |
| Operating Junction Temperature Range | T_J | -65 to +150 | | | | | | | | $^\circ\text{C}$ |
| Storage Temperature Range | T_{STG} | -65 to +175 | | | | | | | | $^\circ\text{C}$ |

- Notes:
1. 2.0us Pulse Width, $f=1.0\text{ KHz}$
 2. Pulse Test: 300us Pulse Width, 1% Duty Cycle
 3. Thermal Resistance from Junction to Case Per Leg, with Heatsink size (4"x6"x0.25") Al-Plate.

RATINGS AND CHARACTERISTIC CURVES (MBRF3035CT THRU MBRF30150CT)

FIG.1- FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT PER LEG




FIG.3- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS PER LEG




FIG.4- TYPICAL REVERSE CHARACTERISTICS PER LEG




FIG.5- TYPICAL JUNCTION CAPACITANCE PER LEG




FIG.6- TYPICAL TRANSIENT THERMAL IMPEDANCE PER LEG

