


MPH/ MPL

+105°C Metallized Polypropylene Capacitors



Energized by ICEL High frequency, high current applications

FEATURES

- High ripple current ratings
- Low ESR
- Stable capacitance versus frequency and temperature

SPECIFICATIONS

Capacitance Tolerance	±10% (K) at 1kHz, 20°C	
Operating Temperature Range	-55°C to 105°C	
Voltage Range	100 WVDC to 400 WVDC	
Dissipation Factor	<0.1% @1kHz	
Insulation Resistance	≥200,000 MΩ x μF not to exceed 400,000MΩ	
Load Life	1,000 hours, +85°C with 125% Rated WVDC	
	Capacitance Change	≤±3% of initial readings @+25°C, 1kHz
	Dissipation Factor	≤.1% of initial reading at 1kHz @ +25°C
	Insulation Resistance	≥50% of minimum initial limit @ +25°C
Self-inductance	≤ 1nH/mm along the capacitor body and leads	
Capacitance Drift Factor	±1.0% (after 2 years)	
Maximum Pulse Rise Time	10 v/μ sec.	

PERFORMANCE RATING/TEST

RATED DC WORKING VOLTAGE (WVDC)

IC Type MPH and MPL capacitors are designed to operate at the specified rated maximum DC Working Voltage over a temperature range of -55°C to +105°C. Operation at temperatures up to and including +105°C are permissible without derating.

Operating Temperature	DC Voltage Rating
+25°C	100%
+85°C	100%
+105°C	100%

DIELECTRIC STRENGTH

160% rated DC voltage is applied for 2 seconds at +25°C


INSULATION STRENGTH

Terminal to Terminal: 100 VDC for 1 minute at 25°C (±).
Units will meet Insulation Resistance requirements

Humidity/Shelf Life Test, 21 days, 95%RH, +40°C and no applied voltage	
Capacitance Change	≤2% of initial readings @ 25°C, 1kHz
Dissipation Factor Change	≤.1% of initial readings @+25°C, 1kHz
Insulation Resistance	≥50% of minimum initial

CONSTRUCTION

Type	Extended metallized film
Dielectric	Polypropylene film
Electrodes	Vacuum deposited aluminum layers
Leads	Tinned copper wire(MPH or tinned copper lugs (MPL))
Coating	Flame retardant polyester tape wrap (UL510) with epoxy end seals UL94V-0



Extended metallized film design

STANDARD PART LISTING

MPL

Capacitance (µf)	WVDC	iC [®] PART NUMBER	Maximum E.S.R. (mΩ)	Maximum Ripple Current Amperes RMS (20kHz-100kHz)							D Max.	L Nominal	L1 Nominal	c Nominal
				+25°C	+35°C	+45°C	+55°C	+65°C	+75°C	+85°C				
1.0	100	105MPL100K	15	10.3	9.5	8.7	7.8	6.7	5.5	5.0	13.5	25.5	41.7	38.5
1.0	200	105MPL200K	20	7.3	7.3	7.3	7.3	7.3	6.4	5.8	13.0	37.5	54.4	45.5
1.0	400	105MPL400K	19	9.5	9.5	9.5	9.5	9.5	8.3	7.5	18.1	44.5	60.7	51.5
2.0	100	205MPL100K	12	12.0	11.0	10.0	8.9	7.8	6.3	5.8	15.2	30.5	46.4	38.5
2.0	200	205MPL200K	15	14.3	13.2	12.1	10.8	9.4	7.7	7.0	17.7	37.5	54.4	45.5
2.0	400	205MPL400K	15	15.0	15.0	15.0	14.2	12.3	10.0	9.1	22.7	50.5	67.1	55.5
3.0	100	305MPL100K	11	13.3	12.3	11.2	10.0	8.7	7.1	6.5	18.2	30.5	46.4	38.5
3.0	200	305MPL200K	13	15.9	14.7	13.5	12.0	10.4	8.5	7.8	19.0	44.5	60.7	51.5
3.0	400	305MPL400K	12	21.1	19.5	17.8	15.9	13.8	11.3	10.3	27.6	50.5	67.1	55.5
5.0	100	505MPL100K	10	14.8	13.7	12.5	11.2	9.7	7.9	7.2	18.6	37.5	54.4	45.5
5.0	200	505MPL200K	11	18.3	17.0	15.5	13.9	12.0	9.8	8.9	21.9	50.5	67.1	55.5
5.0	400	505MPL400K	10	24.4	22.6	20.6	18.5	16.0	13.1	11.9	30.3	63.5	79.8	69.5
10.0	100	106MPL100K	9	17.8	16.5	15.0	13.5	11.7	9.5	8.7	22.8	44.5	60.7	51.5
10.0	200	106MPL200K	9	22.4	20.7	18.9	16.9	14.6	12.0	10.9	26.2	63.5	79.8	55.5
10.0	400	106MPL400K	6	30.0	27.8	25.4	22.7	19.7	16.1	14.7	42.4	63.5	79.8	69.5
20.0	100	206MPL100K	8	21.6	20.0	18.3	16.4	14.2	11.6	10.6	25.4	63.5	79.8	69.5
20.0	200	206MPL200K	6	27.4	25.4	23.2	20.7	17.9	14.7	13.4	36.6	63.5	79.8	69.5
30.0	100	306MPL100K	6	24.3	22.5	20.5	18.4	15.9	13.0	11.9	30.5	63.5	79.8	69.5

NOTE: ESR MAXIMUM EQUIVALENT SERIES RESISTANCE FOR FREQUENCIES ≥ 100 kHz. (mm) Convert to inches divide by 25.4

