

MILL-MAX PLCC Sockets



STANDARD PLCC SOCKETS



RoHS Compliant

Specifications:

- Contacts: 150 μ m Tin
- Insulator: PPS Polyphenylene Sulfide, Rated UL94V-0
- Current rating: Thru-hole type 1A, SMD type 1A
- Shell Plating: 200 μ m (matte finish) over 100 μ m Nickel
- Inner Contact Planting: 100 μ m (matte finish) over 50 μ m Nickel

- Operating Temp: -55° to +105° C
- Contact Pressure: 150 grams min.
- Capacitance: 1pF max.

DIMENSIONS: in.

For quantities of 5000 and up, call for quote.

MOUSER STOCK NO.	Mill-Max Part No.	No. of Pins	Fig.	Dimensions: in.			Price Each				
				A	B	C	1	10	100	500	1000
Through Board Mount											
575-202444	940-44-020-24-000000	20	A	.613	.200	.400	1.06	1.01	.88	.79	.71
575-942824	940-44-028-24-000000	28	A	.713	.300	.500	1.06	1.01	.89	.80	.71
575-943224*	940-44-032-24-000000	32	A	.813/.713	.400/.300	.600/.500	1.06	1.01	.89	.80	.71
575-944424	940-44-044-24-000000	44	A	.913	.500	.700	1.06	1.01	.89	.80	.71
575-945224	940-44-052-24-000000	52	A	1.013	.600	.800	1.13	1.07	.94	.85	.75
575-682444	940-44-068-24-000000	68	A	1.213	.800	1.000	1.36	1.29	1.14	1.02	.91
575-948424	940-44-084-24-000000	84	A	1.413	1.000	1.200	1.51	1.43	1.26	1.13	1.01
Surface Mount											
575-942017	940-44-020-17-400000	20	B	.613	.200	.334	1.04	.98	.86	.78	.69
575-942817	940-44-028-17-400000	28	B	.713	.300	.434	1.07	1.01	.89	.80	.71
575-943217*	940-44-032-17-400000	32	B	.813/.713	.400/.300	.534/.434	1.11	1.05	.92	.83	.74
575-944417	940-44-044-17-400000	44	B	.900	.500	.634	1.15	1.09	.96	.86	.77
575-945217	940-44-052-17-400000	52	B	1.013	.600	.734	1.25	1.19	1.04	.94	.83
575-946817	940-44-068-17-400000	68	B	1.213	.800	1.000	1.57	1.49	1.31	1.17	1.04
575-948417	940-44-084-17-400000	84	B	1.413	1.000	1.200	1.72	1.64	1.44	1.29	1.15

* Rectangular

