



CABLE

PVC round cable LIYY 2x0.14mm², 350V
colour grey, colour of wires brown/white
ends 5±1 mm stripped and tinned

*PVC Rundkabel LIYY 2x0.14 mm², 350V
Mantelfarbe grau, Aderfarben braun/weiss
Enden 5±1 mm abisoliert und verzinkt*

MATERIAL

stem- polypropylene white
nut- polypropylene white
float- polypropylene white
O-ring- nitril cautchuc black

*Schaft- Polypropylen weiss
Mutter- Polypropylen weiss
Schwimmer- Polypropylen weiss
O-Ring nitril Kautschuk schwarz*

Float specific density - approx. 0.7 g/cm³
Spezifisches Schwimmergewicht ca. 0.7 g/cm³

MARKING

MEDER-Label, Type
Production code EN60062/
Factory code

*MEDER-Logo, Typ
Produktionscode
EN60062/Fertigungsstätte*



dimensions / Abmessungen (mm)
unspecified tolerances acc. to DIN ISO 2768-m

Special Product Data	Conditions	Min	Typ	Max	Unit
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			10	W
operating voltage	DC or Peack AC			320	VDC
operating ampere	DC or Peack AC			1	A
Switching current	DC or Peack AC			0,4	A
Sensor-resistance	measured with 40% overdrive			400	mOhm
Housing material				PP	
Case color				white	
Sealing compound				Polyurethan	

Environmental data	Conditions	Min	Typ	Max	Unit
Operating temperature	cabale not moved	-30		80	°C
Operating temperature	cabale moved	-5		80	°C
Storage temperature		-30		80	°C
safety class	DIN EN 60529			IP68, until the thread	

Cable specification	Conditions	Min	Typ	Max	Unit
Cable typ				round cable	
Cable material				PVC	
Cross section				0,14 qmm	

General data	Conditions	Min	Typ	Max	Unit
Mounting advice				over 5m cable, a series resistor is recommended.	
Tightening torque				3	Nm