

Part Number: C2409A

Revision

Date:

7/12/2012

2C/14 19/.0147TC UNSH PVC / PVC

COMMUNICATION & CONTROL CABLE

A. CONSTRUCTION

Conductor: 14 AWG 19/.0147 TC
 Insulation: .030" Wall, Polyvinyl Chloride
 Cable Core: 2C @ 6.00" LHL
 Jacket: .032" Wall, Polyvinyl Chloride (PVC)
 Print Legend: **CAROL (R) 14 AWG -- C2409A -- 75C E60233-8 (UL)
 CL3 OR AWM STYLE 2587 --- CSA LL69381 CMH --
 MADE IN USA (Date code) (Seq Footage)**

DIAMETERS

.071" nom
 .131" nom
 .262" nom
 .326" nom

B. INDUSTRY APPROVALS

National Electrical Code	Article 725
UL Standard 13	Type CL3
UL Standard 758	AWM Style 2587
CSA International	Type CMH

C. ELECTRICAL PROPERTIES

Temperature: 75C
 Suggested Working Voltage: 300V
 Conductor DCR: 2.7 Ohms/1000 ft nom
 Mutual Capacitance: 29 pF/ft @ 1kHz nom

D. COLOR CODE

Cond	COLOR
1	BLACK
2	WHITE