

Part Number: C0843A

Revision: 11/13/2012

**3P 24AWG (7/32) TC PE, OAS, PVC**

**COMPUTER CABLE**

**A. CONSTRUCTION**

Conductor:	#24 AWG (7/32) Tinned Copper	.023" Nom
Insulation:	.024" Wall, Polyethylene (PE)	.071" Nom
Pair:	2 conductors @ 1.75" LHL	.142" Nom
Cable:	3 pairs @ 3.00" LHL	
Overall Shield:	Aluminum/polyester tape (foil out) with a #24 AWG (7/32)TC Drain Wire	.274" Nom
Braid:	Tinned copper braid shield, 90% coverage	.296" Nom
Jacket:	.032" Wall, Polyvinyl Chloride (PVC)	.360" +/- 0.018"
Print Legend:	<b>CAROL (R) 24 AWG - - C0843A - - 75C E105765-H CM(UL) C(UL) CMH OR 80C AWM STYLE 2919 30V LOW VOLTAGE COMPUTER CABLE - - MADE IN USA (DATE CODE) (SEQUENTIAL FOOTAGE)</b>	

**DIAMETERS**

**B. INDUSTRY APPROVALS**

National Electrical Code	Article 800
UL Standard 444	Type CM, CMH
UL Standard 758	AWM Style 2919

**C. ELECTRICAL PROPERTIES**

Temperature:	-20°C to +80°C
Suggested Working Voltage:	300V Max
Conductor DCR:	27.7 Ohms/M' @ 20°C (Max)
Mutual Capacitance:	11.7 pF/ft @ 1kHz (nom)
Ground Capacitance:	21.0 pF/ft @ 1kHz (nom)
Characteristic Impedance:	120 Ohms @ 1MHz (nom)

**D. COLOR CODE**

PAIR	COLOR
1	BLACK - RED
2	BLACK - WHITE
3	BLACK - GREEN

**E. CUSTOMER APPROVAL**

Signature: \_\_\_\_\_  
 Date: \_\_\_\_\_