



Part No.	Emitting Color + Material	λ D (nm)	Lens Type	Iv (mcd) @20mA		Viewing Angle 2θ1/2	Dimension
				Min.	Typ.		

L5LEGW12.3SF	GaAsP/GaP	625	white diffused	20	60	60°	T-1 3/4 (5mm) Round
	GaP	568		20	50		
L5LEYW12.3SF	GaAsP/GaP	625	white diffused	20	60	60°	
	GaAsP/GaP	588		20	40		
L5LGW12.3SF	GaP	568	white diffused	20	50	60°	
	GaAsP/GaP	588		20	40		

L159TEEC	GaAsP/GaP	625	water clear	80	150	40°	T-1 3/4 (5mm) Round
	GaAsP/GaP	625		80	150		
L159TYYC	GaAsP/GaP	588	water clear	60	100	40°	
	GaAsP/GaP	588		60	100		
L159TSGSGC	GaP	568	water clear	80	150	40°	
	GaP	568		80	150		
L159TSR SRC	GaAlAs	640	water clear	500	1000	40°	
	GaAlAs	640		500	1000		

L161TEEC	GaAsP/GaP	625	water clear	100	200	45°(H) 25°(V)	T-1 3/4 (5mm) Oval
	GaAsP/GaP	625		100	200		
L161TYYC	GaAsP/GaP	588	water clear	100	150	45°(H) 25°(V)	
	GaAsP/GaP	588		100	150		
L161TSGSGC	GaP	568	water clear	100	200	45°(H) 25°(V)	
	GaP	568		100	200		
L161TSR SRC	GaAlAs	640	water clear	500	1300	45°(H) 25°(V)	
	GaAlAs	640		500	1300		

L1619URURC/CA	GaAlAs	640	water clear	480	1300	60°(H) 30°(V)	T-1 3/4 (5mm) Oval
	GaAlAs	640		480	1300		

NOTES :

- All dimensions are in millimeters (inches)
- Tolerance is ±0.25mm(0.01") unless otherwise noted.