BGA Heat Sink (High Aspect Ratio Ext.) **Custom Pin Fin**



ATS Part#:

Description:

Heat Sink Type:

ATS045045012-PF-15K

45.00 x 45.00 x 12.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin

Heat Sink Attachment: Equivalent Part Number: N/A

Custom Pin Fin

N/A

*Image above is for illustration purpose only.

Features & Benefits

- · High efficiency pin fin design provides low pressure drop characteristics
- Large surface area increases heat sink performance .
- . Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option ٠

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	4.63 °C/W	3.1 °C/W	2.5 °C/W	2.1 °C/W	1.9 °C/W	1.8 °C/W	1.6 °C/W
	Ducted Flow	2.1	1.8	1.6	1.4	1.3	1.2	1.2

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	тім	Finish
Alta	45.00 mm	45.00 mm	12.00 mm	45 mm	N/A	BLACK-ANODIZED
Image above is for illustration purpose only.	 Dimensior Dimensior Thermal p application ATS reserve performan ATS certification 	 D is fin tip to fin tip performance data are n. a. b. the right to update b. the right to update 	e provided for refere ate or change its pro	m of the base to the nce only. Actual perf ducts without notice 6-6 and REACH com ble.	formanc to impr	e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA