



DUAL-IN-LINE SOCKETS Surface Mount, Stub Tail, with Alignment Pins for Hand Placement

Series 113

- Unique floating contacts compensate for effects of unevenly dispensed solder paste.
- Two corner alignment pins (power & ground positions) permit manual placement.
- High temperature insulator can withstand infra-red reflow and vapor phase soldering.
- Hi-Rel, 4-finger BeCu #30 clip rated at 3 amps. See page 208 for details.
- Uses Mill-Max #1334 & 1434 pins. See pages 140 & 131.

Total number of pins				Quantity per tube	Ordering Information
	A	B	C		
10	0.5	0.2	0.3	41	113-93-210-41-117
4	0.2	0.3	0.4	100	113-93-304-41-117
6	0.3	0.3	0.4	67	113-93-306-41-117
8	0.4	0.3	0.4	50	113-93-308-41-117
10	0.5	0.3	0.4	40	113-93-310-41-117
14	0.7	0.3	0.4	28	113-93-314-41-117
16	0.8	0.3	0.4	25	113-93-316-41-117
18	0.9	0.3	0.4	22	113-93-318-41-117
20	1.0	0.3	0.4	20	113-93-320-41-117
22	1.1	0.3	0.4	18	113-93-322-41-117
24	1.2	0.3	0.4	16	113-93-324-41-117
28	1.4	0.3	0.4	14	113-93-328-41-117
20	1.0	0.4	0.5	20	113-93-420-41-117
22	1.1	0.4	0.5	18	113-93-422-41-117
24	1.2	0.4	0.5	16	113-93-424-41-117
28	1.4	0.4	0.5	14	113-93-428-41-117
32	1.6	0.4	0.5	12	113-93-432-41-117
24	1.2	0.6	0.7	16	113-93-624-41-117
28	1.4	0.6	0.7	14	113-93-628-41-117
32	1.6	0.6	0.7	12	113-93-632-41-117
36	1.8	0.6	0.7	11	113-93-636-41-117
40	2.0	0.6	0.7	10	113-93-640-41-117
42	2.1	0.6	0.7	9	113-93-642-41-117
48	2.4	0.6	0.7	8	113-93-648-41-117
50	2.5	0.6	0.7	8	113-93-650-41-117
52	2.6	0.6	0.7	7	113-93-652-41-117
50	2.5	0.9	1.0	8	113-93-950-41-117
52	2.6	0.9	1.0	7	113-93-952-41-117
64	3.2	0.9	1.0	6	113-93-964-41-117
PLATING CODE =					93
Sleeve (Pin)					200μ" Sn/Pb
Contact (Clip)					30μ" Au