



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. GOLD PL. 30 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 5. TEFLON MIL-P-19468

8	COVER	NOTE 2	NOTE 3	1	CV-5X05-T
7	HOUSING	NOTE 1	NOTE 3	1	SMB4073A1-9
6	CONTACT PIN	NOTE 1	NOTE 4	1	SMB4073A1-8
5	INSULATOR	NOTE 5	NATURAL	2	SMB4073A1-7T-50
4	BODY	NOTE 1	NOTE 3	2	SMB4073A1-6
3	CONTACT PIN	NOTE 1	NOTE 4	1	SMB1112A1-4
2	INSULATOR	NOTE 5	NATURAL	1	SMB3073A1-2T-50
1	BODY	NOTE 1	NOTE 3	1	SMB1112A1-2
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS			PART NO.	SMB3073A1-3GT30G-50
UNLESS OTHERWISE SPECIFIED TOLERANCES			APPROVED	DATE
0.5-6	= ±0.2			10-11-01'
6-30	= ±0.4		CHECKED	DATE
30-120	= ±0.6			10-11-01'
120-315	= ±1		DRAWN	DATE
315-1000	= ±1.6			10-11-01'
1000-2000	= ±2.4		FILE NO.	

Amphenol	
TITLE SMB "T" ADAPTOR JACK-JACK-JACK	
DRAWING NO.	
ITEM NO.	