


20A SCHOTTKY BARRIER DIODE

Full Pack High Voltage Schottky Rectifier MBRF20100CT THRU MBRF20200CT


Formosa MS

Specification Features:

- High Voltage Wide Range Selection, 100V, 150V & 200V
- High Switching Speed Device
- Low Forward Voltage Drop
- Low Power Loss and High Efficiency
- Guard Ring for Over-voltage Protection
- High Surge Capability
- RoHS Compliant
- Matte Tin(Sn) Lead Finish
- Terminal Leads Surface is Corrosion Resistant and can withstand to 260°C Wave Soldering or per MIL-STD-750, Method 2026.



POLARITY CONFIGURATION



MAXIMUM RATINGS (Per Leg, unless otherwise specified)

Symbol	Parameter	MBRF20100CT	MBRF20150CT	MBRF20200CT	Units
V_{RRM} V_{RWM} V_R	Maximum Repetitive Reverse Voltage Working Peak Reverse Voltage Maximum DC Reverse Voltage	100	150	200	V
$I_{F(AV)}$	Average Rectified Forward Current Per Leg Per Package		10 20		A
I_{FSM}	Non-repetitive Peak Forward Surge Current 8.3mS Single Phase @ Rated Load		150		A
T_{STG}	Storage Temperature Range		-65 to +150		°C
T_J	Operating Junction Temperature		+150		°C

These ratings are limiting values above which the serviceability of the diode may be impaired.

THERMAL CHARACTERISTICS $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Value	Units
$R_{\theta JC}$	Maximum Thermal Resistance, Junction-to-Case	2.0	°C/W
$R_{\theta JA}$	Maximum Thermal Resistance, Junction-to-Ambient (per leg)	60	°C/W

ELECTRICAL CHARACTERISTICS (Per Diode) $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Condition (Note 1)	MBRF20100CT		MBRF20150CT		MBRF20200CT		Units
			Min	Max	Min	Max	Min	Max	
I_R	Reverse Current	@ rated V_R	---	200	---	200	---	200	μA
V_F	Forward Voltage	$I_F = 10\text{A}$	---	0.85	---	0.92	---	1.00	V
		$I_F = 20\text{A}$	---	0.95	---	1.00	---	1.25	

Note/s:

- Tested under pulse condition of 300 μs .

20A SCHOTTKY BARRIER DIODE

Full Pack High Voltage Schottky Rectifier
 MBRF20100CT THRU MBRF20200CT

Formosa MS

TYPICAL CHARACTERISTICS

Figure 1. Forward Current Derating Curve (Per Diode)




Figure 2. Junction Capacitance (Per Diode)




Figure 3. MBRF20100CT Typical Reverse Current (Per Diode)




Figure 4. MBRF20150CT Typical Reverse Current (Per Diode)




Figure 5. MBRF20200CT Typical Reverse Current (Per Diode)





Figure 6. MBRF20100CT Typical Forward Voltage (Per Diode)





20A SCHOTTKY BARRIER DIODE

Full Pack High Voltage Schottky Rectifier
 MBRF20100CT THRU MBRF20200CT


Formosa MS

Figure 7. MBRF20150CT Typical Forward Voltage (Per Diode)

Figure 8. MBRF20200CT Typical Forward Voltage (Per Diode)



TO220FP SG PACKAGE OUTLINE



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A1	2.7	3.3	0.106	0.130
A2	15.0	15.7	0.591	0.618
A4	6.2	6.6	0.244	0.260
b	0.5	0.9	0.020	0.035
b1	0.9	1.2	0.035	0.047
b2	1.0	1.2	0.039	0.047
c	0.4	0.6	0.016	0.024
D	9.8	10.3	0.386	0.406
e	2.34	2.74	0.092	0.108
E	4.3	4.6	0.169	0.181
E1	2.5	2.9	0.098	0.114
F	2.6	3.0	0.102	0.118
L	10.3	10.7	0.406	0.421
ØP	3.0	3.4	0.118	0.134
Q	2.3	2.7	0.091	0.106