

# New Jersey Semi-Conductor Products, Inc.

20 STERN AVE.  
SPRINGFIELD, NEW JERSEY 07081  
U.S.A.

TELEPHONE: (973) 376-2922  
(212) 227-6005  
FAX: (973) 376-8960

## SWITCHMODE SERIES NPN POWER TRANSISTORS

... designed for use in high-voltage, high-speed, power switching in inductive circuit, they are particularly suited for 115 and 220 V switchmode applications such as switching regulator's, inverters, DC-DC converter, Motor controls, Solenoid / Relay drivers and Deflection circuits.

### FEATURES:

\*Collector-Emitter Sustaining Voltage-

$$V_{CE(SUS)} = 400 \text{ V and } 300 \text{ V}$$

\*Collector-Emitter Saturation Voltage -

$$V_{CE(SAT)} = 1.0 \text{ V (Max.) @ } I_C = 4.0 \text{ A, } I_B = 1.0 \text{ A}$$


\* Switching Time -  $t_f = 0.9 \text{ us (Max.) @ } I_C = 2.0 \text{ A}$

### MAXIMUM RATINGS

Characteristic	Symbol	MJE13004	MJE13005	Unit
Collector-Emitter Voltage	$V_{CEO}$	300	400	V
Collector-Emitter Voltage	$V_{CEV}$	600	700	V
Emitter-Base Voltage	$V_{EBO}$	9.0		V
Collector Current - Continuous	$I_C$	4.0		A
- Peak	$I_{CM}$	8.0		
Base current	$I_B$	2.0		A
Total Power Dissipation @ $T_C = 25^\circ\text{C}$	$P_D$	75		W
Derate above $25^\circ\text{C}$		0.6		W/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	$T_J, T_{STG}$	-65 to +150		$^\circ\text{C}$

### THERMAL CHARACTERISTICS


Characteristic	Symbol	Max	Unit
Thermal Resistance Junction to Case	$R_{\theta jc}$	1.67	$^\circ\text{C/W}$




NPN

MJE13004  
MJE13005

4 AMPERE  
POWER  
TRANSISTORS  
300-400 VOLTS  
75 WATTS



TO-220



PIN 1.BASE  
2.COLLECTOR  
3.EMITTER  
4.COLLECTOR(CASE)

DIM	MILLIMETERS	
	MIN	MAX
A	14.68	15.31
B	9.78	10.42
C	5.01	6.52
D	13.06	14.62
E	3.57	4.07
F	2.42	3.66
G	1.12	1.36
H	0.72	0.96
I	4.22	4.98
J	1.14	1.38
K	2.20	2.97
L	0.33	0.55
M	2.48	2.98
O	3.70	3.90



NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However, NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.

Quality Semi-Conductors

**ELECTRICAL CHARACTERISTICS** (  $T_C = 25^\circ\text{C}$  unless otherwise noted )

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

**OFF CHARACTERISTICS**

Collector-Emitter Sustaining Voltage ( $I_C = 10\text{ mA}$ , $I_B = 0$ ) MJE13004 MJE13005	$V_{CE(sus)}$	300 400		V
Collector Cutoff Current ( $V_{CEV} = \text{Rated Value}$ , $V_{BE(off)} = 1.5\text{ V}$ ) ( $V_{CEV} = \text{Rated Value}$ , $V_{BE(off)} = 1.5\text{ V}$ , $T_C = 100^\circ\text{C}$ )	$I_{CEV}$		1.0 5.0	mA
Emitter Cutoff Current ( $V_{EB} = 9.0\text{ V}$ , $I_C = 0$ )	$I_{EBO}$		1.0	mA

**ON CHARACTERISTICS (1)**

DC Current Gain ( $I_C = 1.0\text{ A}$ , $V_{CE} = 5.0\text{ V}$ ) ( $I_C = 2.0\text{ A}$ , $V_{CE} = 5.0\text{ V}$ )	hFE	10 8.0	60 40	
Collector-Emitter Saturation Voltage ( $I_C = 1.0\text{ A}$ , $I_B = 200\text{ mA}$ ) ( $I_C = 2.0\text{ A}$ , $I_B = 500\text{ mA}$ ) ( $I_C = 4.0\text{ A}$ , $I_B = 1.0\text{ A}$ )	$V_{CE(sat)}$		0.5 0.6 1.0	V
Base-Emitter Saturation Voltage ( $I_C = 1.0\text{ A}$ , $I_B = 200\text{ mA}$ ) ( $I_C = 2.0\text{ A}$ , $I_B = 500\text{ mA}$ )	$V_{BE(sat)}$		1.2 1.6	V

**DYNAMIC CHARACTERISTICS**

Current Gain - Bandwidth Product ( $I_C = 500\text{ mA}$ , $V_{CE} = 10\text{ V}$ , $f = 1.0\text{ MHz}$ )	$f_T$	4.0		MHz
---	-------	-----	--	-----

**SWITCHING CHARACTERISTICS**

Delay Time	$V_{CC} = 125\text{ V}$ , $I_C = 2.0\text{ A}$ $I_{B1} = -I_{B2} = 0.4\text{ A}$ , $t_p = 25\text{ us}$ , Duty Cycle $\leq 1.0\%$	$t_d$	0.1	us
Rise Time		$t_r$	0.7	us
Storage Time		$t_s$	4.0	us
Fall Time		$t_f$	0.9	us

(1) Pulse Test: Pulse Width = 300 us, Duty Cycle  $\leq 2.0\%$

**TO-220 MECHANICAL DATA**

DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A	4.40		4.60	0.173		0.181
C	1.23		1.32	0.048		0.051
D	2.40		2.72	0.094		0.107
D1		1.27			0.050	
E	0.49		0.70	0.019		0.027
F	0.61		0.88	0.024		0.034
F1	1.14		1.70	0.044		0.067
F2	1.14		1.70	0.044		0.067
G	4.95		5.15	0.194		0.203
G1	2.4		2.7	0.094		0.106
H2	10.0		10.40	0.393		0.409
L2		16.4			0.645	
L4	13.0		14.0	0.511		0.551
L5	2.65		2.95	0.104		0.116
L6	15.25		15.75	0.600		0.620
L7	6.2		6.6	0.244		0.260
L9	3.5		3.93	0.137		0.154
DIA.	3.75		3.85	0.147		0.151

